





PRODUCT DESCRIPTION

Soft oval forms offer a modern and playful touch to this LED wall mounted sconce. The face of the fixture is a light guided White acrylic diffuser that even illuminates the edge-lit LED light source. The sleek shape is made even more attractive by the bright illumination provided by the fixture itself. Great for use in bathrooms or corridors, the fixture is ADA compliant and available in 4 lengths. A recessed housing behind the fixture not only mounts the fixture with an attractive extension that makes it appear to be floating off the wall, but it also features a 5-step color temperature select switch allowing you to discreetly adjust the LED lighting to 5 settings ranging from a warmer 2700K to 3000-3500-4000 and daylight white 5000K. These additional product features thereby give more latitude to the design applications without special requests.

MEASUREMENTS

DIMENSION : 24" W x 5" H x 2.5" Ext **BACK PLATE** : 4" W x 13.5" H x 12" HCO

: 3.96 lb HANGING WEIGHT

LAMPING

INPUT VOLTAGE : 120V

LUMENS : 2,000 Rated (1,350 Del.)

BULB : 1 x 20W LED AC Integrated, 20W Total

BULB INCLUDED : (Integrated) : Triac or ELV DIMMABLE CRI : 90 CRI

COLOR_TEMP : CCT Select 5KK

LIGHTING_DIRECTION: Backlit

FINISHES OPTION

Black (BK)

Gold (GLD)

Polished Chrome (PC)

Satin Nickel (SN)

MATERIAL

Aluminum, Polycarbonate

RATINGS

cETLus Damp Location ADA







ADDITIONAL

INSTALL UP/DOWN: Horizontal/Vert RATED LIFE 35000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER) 253 NORTH VINELAND AVE I CITY OF INDUSTRY, CA 91746

EASTERN DISTRIBUTION CENTER

101 GARDNER PARK | PEACHTREE CITY, GA 30269

P. 626.956.4200 | F. 626.956.4225 | maximlighting.com