

LED Wraparound

Damp Rated, 130 lm/W, Dimmable

FEATURES

| | |
|----------------------|---------------------|
| Lumen Output | 2860 to 5200 lumens |
| Efficacy | 130 lm/W |
| Input Voltage | 120-277V |
| Dimmable | 0-10V Continuous |
| Size | 4-FT |
| CCT | 4000K, 5000K |
| Rating | Damp Location |
| Warranty | 7 Years |

APPLICATIONS

Premium indoor luminaire suitable for general indoors, lobbies, offices, meeting rooms, restrooms, hallways, stairwells, storage-closets, kitchens, and work-stations.

CONSTRUCTION

Manufactured for durability using aluminum sheet housing with semi-gloss coating to resist corrosion, discoloration, and scratching. Damp Location rated.

ELECTRICAL

Input voltages 120-277V models with 0-10V Continuous Dimming. Operating temperatures -4°F to 122°F (-20°C to 50°C).

MOUNTING

Surface Mounting on ceilings or beams.

OPTICS

Anti-UV Frosted Prismatic Polycarbonate Lens standard.

LISTINGS

DLC listed. UL certified to meet US and Canadian standards. FCC and RoHS compliant.

WARRANTY

7 year exclusive limited warranty.

| |
|--------------|
| Project: |
| Date: |
| Catalog No: |
| Prepared By: |



4-FT Models



CORRELATED COLOR TEMPERATURES (CCT)

4000K

5000K



SPECIFICATIONS

ENERGY DATA

Input Voltage: 120-277V
Input Frequency: 50/60 Hz
Wattage: 22W, 40W
Power Factor: >0.9
Total Harmonic Distortion (THD): <10%
Operating Temperature: -4°F to 122°F (-20°C to 50°C)

LIGHTING DATA

Lumens: 2860 to 5200
Lumens Per Watt: 130 lm/W
Correlated Color Temperature (CCT): 4000K, 5000K
Dimmable: 0-10V
Color Rendering Index (CRI): >82
L70: 75000 hours

ORDERING INFORMATION

| Model | Size | Wattage | Voltage | Current | Lumens | Efficacy | CCT | Dimming | Color | Dimensions |
|------------------|------|---------|----------|------------------------|--------|----------|-------|---------|-------|---------------------------|
| ETH-WRP-4-22W-4K | 4-FT | 22W | 120-277V | 0.18A@120V, 0.08A@277V | 2860 | 130 lm/W | 4000K | 0-10V | White | 47.75"L x 7.12"W x 2.80"H |
| ETH-WRP-4-22W-5K | 4-FT | 22W | 120-277V | 0.18A@120V, 0.08A@277V | 2860 | 130 lm/W | 5000K | 0-10V | White | 47.75"L x 7.12"W x 2.80"H |
| ETH-WRP-4-40W-4K | 4-FT | 40W | 120-277V | 0.33A@120V, 0.14A@277V | 5200 | 130 lm/W | 4000K | 0-10V | White | 47.75"L x 7.12"W x 2.80"H |
| ETH-WRP-4-40W-5K | 4-FT | 40W | 120-277V | 0.33A@120V, 0.14A@277V | 5200 | 130 lm/W | 5000K | 0-10V | White | 47.75"L x 7.12"W x 2.80"H |

PHYSICAL DIMENSIONS

4-FT Model

47.75"L x 7.12"W x 2.80"H

