


FLV12 SERIES OUTDOOR LIGHTING

FLV12-12W-30K
FLV12-12W-50K

Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



Selection:

7 1/2"(H) x 4"(W) x 5 3/4"(D)

The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Features

- Die-cast Aluminum Housing with Powder Coat Finish (Dark Bronze)
- 1/2" Threaded Knuckle Stem
- 7-Year Warranty
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors

Technical Specifications

Electrical:

- Voltage: 12V AC/DC
- Power Factor: >0.9
- Wattage: 12W
- Input current: 1A Max
- Efficacy: 100/ 108 LPW

Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish (Dark Bronze)
- Solid State Lighting Technology for Long Life, No Maintenance Needed and High-Efficiency
- High Conductive Aluminum LED Board
- 8-1/2" PC Spike Included
- 1/2" Threaded Knuckle Stem
- IP Rating: IP65
- Operating Temperature: -40°F to 104°F
- Suitable for Wet Locations
- Rotatable Shroud with Set Screw
- 7-Year Warranty

Lighting:

- Dimmable: Non Dimmable
- LED type/brand: Lumileds LEDs / SMD 3030
- Total lumens: 1200LM/ 1300LM
- Color Temperatures: 3000K/ 5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 35°
- Lifespan: 70,000 Hrs.

Applications:




- The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Other Models:

- 6W | 500LM | FLV12-6W-30K
- 6W | 550LM | FLV12-6W-50K
- 24W | 2200LM | FLV12-24W-30K
- 24W | 2500LM | FLV12-24W-50K
- 32W | 3200LM | FLV12-32W-30K
- 32W | 3500LM | FLV12-32W-50K



Photometrics: FLV12-12W



BUG Rating: B2-U1-G0

12W 3000K, Area 35'x 35' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: FLV12-12W

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FLV12-12W-30K	12W	12V	1200LM	3000K	B2-U1-G0	100
FLV12-12W-50K	12W	12V	1300LM	5000K	B2-U1-G0	108

Sample Ordering

Model **Watt** **Color Temp.**
 - -
30K = 3000K
50K = 5000K

Accessories:

Blank = No Option For Accessories

- A-41-BR = 1/2" NPT Hub, Cast Aluminum, Bronze Powder Coat Finish
- LSWN1 = Bag of 24, Waterproof Wire Connectors, For Up to Two 14-2 + One 16-2 Cables
- LSWN2 = Box of 24, Waterproof Wire Connectors, For Up to Three 12-2 Cables
- LSWN2-100 = Jar of 100, Waterproof Wire Connectors, For Up to Three 12-2 Cables
- A-41-S = Tree Mounting Base
- LG-SMB-BZ = 12V Brass Landscape Tree or Surface Bracket, Antique Bronze Finish
- BC-13 = 13" Bungee Cords with Hooks
- BC-18 = 18" Bungee Cords with Hooks
- BC-24 = 24" Bungee Cords with Hooks
- BC-32 = 32" Bungee Cords with Hooks
- FL-SH2 = Fits FLD2-28W, FLV12-12W & 24W

ACCESSORIES:



A-41-BR
1/2" NPT hub, Cast aluminum, Bronze Powder coat finish



LSWN1
Bag of 24, Waterproof wire connectors, for up to two 14-2 + one 16-2 cables



LSWN2
Box of 24, Waterproof wire connectors, for up to three 12-2 cables



LSWN2-100
Jar of 100, Waterproof wire connectors, for up to three 12-2 cables



A-41-S
Tree mounting base




LG-SMB-BZ
12V brass landscape tree or surface bracket, antique bronze finish



BC-13/18/24/32
13"/18"/24"/32" Bungee cords with hooks



FL-SH2
Fits FLD2-28W, FLV12-12W & 24W



FL-SH2
4" x 4 1/2"

Example:

1. FLV12-12W-30K-D-KN (FOR FLV12 12W 30K FIXTURE 12V)
2. FLV12-12W-30K-D-KN (FOR FLV12 12W 30K FIXTURE 12V)
FL-SH2 (Fits FLD2-28W, FLV12-12W & 24W)

