

Model No: FI-DOWN-X-XXW-3CCT

# Commercial LED Tunable Down Light

- Available in 6", 8", or 10" sizes
- Aluminum Housing with White Satin Finish
- Frosted Polycarbonate Lens
- Quick Installation Spring Bars
- Tunable Wattage (8W, 12W, or 16W)
- Tunable CCT (3000K, 4000K, or 5000K)



## Performance Data

<b>Voltage:</b>	120-277V
<b>Frequency:</b>	50/60 Hz
<b>CCT:</b>	Tunable (3000K, 4000K, or 5000K)
<b>Efficacy:</b>	Up to 100 lm/W
<b>Dimming:</b>	0-10V
<b>Beam Angle:</b>	80° (6") and 90° (8" & 10")
<b>CRI:</b>	≥ 80
<b>Power Factor:</b>	≥ 0.9
<b>Operating Temp:</b>	77°F (25°C)
<b>Storage Temp:</b>	-4 to 149°F (-20° to 65°C)

**0-10V**  
Dimmable

**IP 54**  
Wet Location

**50K**  
Lifetime Hours



## Ordering Information

Size	Model	Wattage	CCT	Beam Angle
6 in.	FI-DOWN-6-16-3CCT	Tunable 8W, 12W, 16W	Tunable 3000K, 4000K, 5000K	80 Degrees
8 in.	FI-DOWN-8-22-3CCT	Tunable 12W, 16W, 22W	Tunable 3000K, 4000K, 5000K	90 Degrees
10 in.	FI-DOWN-10-33W-3CCT	Tunable 22W, 28W, 33W	Tunable 3000K, 4000K, 5000K	90 Degrees