


PROJECT NAME: _	CATALOG NUMBER:
NOTES:	FIXTURE SCHEDULE:



## **LED Frame Light**











Dimensions (inch)					
L 23 3/4 x W 23 2/4 x H 5/8					
L 47 3/4 x W 23 2/4 x H 5/8					

The LED Frame Light fixture is a new design that delivers innovative and outstanding lighting performance and is designed to replace a drop-in fluorescent light or LED panel. It has a modern design and is easy to install. Ideal for both new construction and remodel/replacement of fluorescent troffers or LED panel in commercial office spaces, schools, healthcare facilities, and retail merchandising areas. This fixture is compact, ultra-thin in appearance, has simple installation, and provides outstanding performance. Available in 2x2 foot and 2x4 foot sizes.

## **FEATURES:**

- CCT Selectable: 3500K / 4000K / 5000K
- Wattage Selectable
  - 2x2: 27W / 35W / 40W2x4: 35W / 45W / 54W
- Lumens
  - o 2x2:
    - 27W: 2700
      - 35W: 3500
      - 40W: 4000
  - o 2x4
- 35W: 3500
- 45W: 4500
- 54W: 5400
- Lumen efficacy: 100Lm/W
- CRI: >80
- Lifetime: 50000 Hours
- Surge protector
- Extruded aluminum with white finish
- Performance lens assembly delivers unique beam angles and reduces glare
- High quality LED Chips provide high efficiency, heat dissipation, stability, and lumen maintenance
- 120-277V 0-10V driver for continuous dimming
- Ambient Temperature: -22°F to +104°F (-30°C to 40°C)
- Damp Location Rated

SKU	Wattage (Lumens)	Efficacy	ССТ	Voltage
GFLED-2X2-CWT-010D-MV	27W (2700) / 35W (3500) / 40W (4000)	100Lm/W	3500K / 4000K / 5000K	120-
GFLED-2X4-CWT-010D-MV	35W (3500) / 45W (4500) / 54W (5400)	100LIII/ W	3300K / 4000K / 3000K	277V



Warehouse-Lighting.com Phone: 888-454-4480 info@warehouse-lighting.com

