



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

Project Name:

Catalog #:

Fixture Schedule:

Notes:



Chain      Pendant

## LED HIGH BAY

*High Bay LED lighting fixtures combine high performance LEDs, and drivers. The GHBLED is the lighting solution for a wide variety of applications and mounting heights. Precision designed optics, multiple distributions, and a choice of lumen outputs and color temperatures make the energy-efficient GHBLED the ideal solution for industrial, commercial, and other high bay applications.*

### FEATURES:

- Wattage: 90W, 145W
- Voltage: 120-277
- CCT options:
  - 4000K or 5000K
- CRI: >80
- Efficacy: 140+ LPW
- Lifespan: 50,000 hours
- Manufacturer warranty: 5 Years
- Driver: 0-10V dimmable LED power supplies, current can be adjusted
- Dimming type is continuous, dimmable to 10%
- Suitable for damp location
- Temperature Rated: -4°F to 120°F
- Optional High Bay motion sensor available
- Multiple mounting options



| Series | Wattage | CRI | Input Voltage | CCT                  | Sensor                             | Option                            |
|--------|---------|-----|---------------|----------------------|------------------------------------|-----------------------------------|
| GHBLED | 90W     | 80+ | 120-277V      | 4000K<br>or<br>5000K | Blank<br>No Sensor                 | EM<br>Emergency Battery<br>Backup |
|        | 145W    |     |               |                      | MS<br>Microwave Sensor             | EMI<br>Factory Installed<br>EM    |
|        |         |     |               |                      | MSR<br>Factory Installed<br>Sensor |                                   |



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

Project Name:

Catalog #:

Fixture Schedule:

Notes:

### Dimensions

| SKU                 | Length | Width | Depth |
|---------------------|--------|-------|-------|
| GHBLED-90W-UNV-40K  | 23.8"  | 13.5" | 3.3"  |
| GHBLED-90W-UNV-50K  |        |       |       |
| GHBLED-145W-UNV-40K |        |       |       |
| GHBLED-145W-UNV-50K |        |       |       |

