WHL-HPEM LED High Performance Emergency Thermoplastic Unit



STANDARD OPTIONAL

ILLUMINATION

- Ultra-bright, energy efficient, long-life White LED adjustable lamp heads provide up to 100-ft center-to-center spacing with a 3-ft path of egress at 7-1/2-ft mounting height.
- High performance chrome-plated metallized reflector and plastic lens.
- 5.0 watt (12 LEDs x 0.42 watt) per head.

ELECTRICAL

- Universal 120-277 voltage.
- Unique bi-color LED indicator light alerts occupant on battery condition (Red-normal, OFF-check battery).
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 9.6V long-life, maintenance-free, rechargeable lithium iron phosphate battery.
- Remote capacity of 3.0 watts standard.
- Internal solid-state transfer switch automatically connects the internal battery to LED lamp heads for minimum 90minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

MOUNTING

- Universal knockout pattern on back plate for surface mount.
- Knockouts provided for conduit feed applications.
- Suitable for wall or ceiling mount.

HOUSING

 Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finish.

ORDERING INFORMATION





Warehouse-Lighting.com 2750 South 163rd St New Berlin, WI 53151 Warehouse-Lighting.com Phone: 888-454-4480 requests@warehouse-lighting.com




OPTIONS


 SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meet electrical and life safety codes.

WARRANTY / LISTING

- Five-year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101, Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under title 20 regulations.

DIMENSIONS





Sample Part Number: WHL-HPEMW

- Models
 WHL-HPEMW (White)
 WHL-HPEMB (Black)
- Options SDT
- LED

5.0W x 2

Spacing

100' x 3' at 7.5-ft MH

- Voltage 120-277V Universal
- Battery
 Lithium Iron Phosphate
- Housing Plastic
- Mounting Wall, Ceiling & Conduit
- Operating Temperature 0°C to 50°C
- UL Listing Damp locations
- Warranty



Warehouse-Lighting.com 2750 South 163rd St New Berlin, WI 53151 Warehouse-Lighting.com Phone: 888-454-4480 requests@warehouse-lighting.com