



PROJECT NAME: _____ CATALOG NUMBER: _____
NOTES: _____ FIXTURE SCHEDULE: _____

**Industrial UV Sanitation Light - Coronavirus - 8000 sq.ft. Area - (16) UVC Lamps - Digital Timer - 304
Stainless Steel - Remote/50' Cord
Item # IND-UC.360-48-8L-UVC-V3-AT-KT-50C**

Ratings/Features:

- Short-wave Germicidal Light
- Kill 99% of viruses and other germs
- Cooling Fans

IND-UC.360-48-8L-UVC-V3-AT-KT-50C UV Sanitation Light

- Lamp Technology: UV-C Fluorescent
- Lamp Qty: (16)
- Dimensions: 28"-W x 28"-D x 68"-H
- Weight: 145 lbs
- Voltage: 120V AC
- Total Watts: 576W
- Single-lamp Watts: 36W
- Total UV Output: 233.6W
- Single-lamp UV Output: 14.6W
- Coverage: 8000 sq. ft.
- Expected Lifespan: 9,000+ Hours
- UV Wavelength: UV-C, 200nm - 280nm (254 nm)
- Lamp Type: T10
- Lamp base: G13
- Beam Angle: 360°
- Light Configuration: Flood
- Setting: Digital Timer
- Delay: 1 Minute and 30 Seconds
- Safety Kit: (4) Warning Signs, (2) Safety Glasses
- Mounting: Portable – 4 wheels attached to bottom
- Wiring: 50' 16/3 SOOW Cord w/ Cord Cap



*****PLEASE NOTE: UV-C light can cause temporary or permanent loss of vision, and temporary acute redness or ulceration (mild to severe sunburn) to exposed skin. To prevent exposure, do not operate the device in any application that allows UV-C light to be visible during operation. NEVER LOOK DIRECTLY AT THE BULB OR DISINFECTING TARGET ZONE. DO NOT touch bulb with bare hands. The oils in your skin will damage the lamp. Fingerprints will result in reduced performance and significantly reduce the lifespan of the lamp unless they are removed with alcohol. Please read instruction manual for UV safety requirements before operating.*****



Applications:

- Sanitation
- Disinfection
- Retail spaces
- Commercial Locations
- Industrial Parks
- Public Transportation (vehicles and hubs)
- Airports
- Office Buildings
- Medical Centers

Additional Features:

- 90 second delay start
- Adjustable timer
- 360° beam angle
- Disinfect 8000 square foot area
- Can be used with room lights on or off
- Can be used in sunlight

Wring/Plug:

This unit is equipped with 50 feet of 16/3 chemical and abrasion resistant SOOW cord that is fitted with an industrial grade cord cap for easy connection to common wall outlets.

Cart:

Operators can easily move the UV lighting system around facilities via four wheels at the bottom. A center rail enables seamless guidance and positioning of the unit. For best results, the light should be setup in the middle of the area.

Note on Environment:

Sunlight and visible light fixtures do not impact the effectiveness of the disinfecting on this UVC sanitation product. Metal halide, high pressure sodium, fluorescent, and LED light fixtures can be left on. The UV radiation emitted from this product is not disrupted by any type of lighting in the environment. Put simply, NO it DOES NOT need to be dark in the area you plan to disinfect. The UV radiation is harmful to the eyes and skin, and that is why you should not be in the area while it is in operation. Please see user manual for additional safety information.



Warehouse-Lighting.com
2750 South 163rd St
New Berlin, WI 53151

Warehouse-Lighting.com
Phone: 888-454-4480
info@warehouse-lighting.com