

EasyLED Series

Bentley EasyLED Small Kitty Hawk Area Light



KH25Q
(Shown with Kitty Hawk Arm.)

Housing:

Die Cast Aluminum Housing and Front Frame, Integral Heat Sinking and Driver Compartment. Powdercoat Finish Over a Chromate Conversion Coating. Photocell Adaptable.

Lens:

Clear Flat Glass Lens or Clear Flat Prismatic Glass Lens

Mounting:

Mounts with Two-Piece Bracket, Yoke, Adjustable Slipfitter, Kitty Hawk Arm, 2 $\frac{3}{8}$ " Diameter Mounting Arm Adapter or Easy Hang Wall Bracket.

LumaFit LED:

Array Lumens:

81w: 10,483 (C Optic); 10,773 (F Optic);

112w: 13,573 (F Optic)

Delivered Lumens:

81w: 6,726 (C, Clear); 9,220 (F, Clear);

7,893 (F, Prismatic)

112w: 9,487 (C, Clear); 10,545 (F, Clear)

CRI: 86

CCT: 4000K, 5000K

Rated Life: 50,000 Hours

5-Year Warranty

Aluminum Boards

Wattage:

81w: Array: 80.5w, System: 86.6w

112w: Array: 111.5w, System: 119.9w

Driver:

Electronic Driver, 120-277V, 50/60Hz or

347/480V, 50/60Hz; Dimmable Driver

Listing & Ratings:

CSA: Listed for Wet Locations. IP67

Operating Temperatures: -40°C to +40°C

LM-79 Report Available on Select Models.

Options:

Surge Protection

Battery Backup

Custom Colors Available Upon Request.



WAREHOUSE-LIGHTING.COM



DesignLights Consortium™ Qualified Luminaires:

KH25QC1X81U5KC***
KH25QF1X81U5KC***
KH25QC1X81U5KC***
KH25QF1X81U5KC***



Bentley EasyLED Small Kitty Hawk Area Light

Catalog #

Description

Complete Units

Ordering Information

Example: KH25QF1X112U5KCZKASP

KH25	Model:	KH25
Q	LED Mfr:	Q=QSSI
F	Optics:	A=Type I, B=Type II, C=Type III, F=Type V
1X	Number of Arrays:	1X=One
112	Wattage:	81=81w, 112=112w
U	Ballast:	U=120-277V, H=347/480V* *81w Model Only
5K	CCT:	4K=4000K, 5K=5000K
C	Lens:	C=Clear Flat Glass Lens, P=Clear Flat Prismatic Glass Lens* *Use with F Optic Only.
Z	Color:	Z=Bronze
KA	Mounting:	BR=Two-Piece Swivel Bracket, Y=Yoke, SF= Slipfitter, MA= Mounting Arm Adapter, KA=Kitty Hawk Arm, EH=Easy Hang Wall Bracket
SP	Options:	SF=Single Fuse, DF=Double Fuse, SP=Surge Protection, AH1=Accessory Housing

LD

LED lighting facts
LED Product Partner

Length with mount (L):


Bracket (BR): 18 $\frac{3}{4}$ "

Yoke (Y): 18"

Slipfitter (SF): 18 $\frac{3}{4}$ "

Mounting Arm Adaptor: 19 $\frac{1}{2}$ "

DIMENSIONS



Catalog #	Description
KH25GLP	Prismatic Flat Glass Lens
FL73BRZ	Two-Piece Swivel Bracket, Stamped Steel, Bronze Powdercoat Finish
FL73SFXZ	External Mount Slipfitter, Die Cast, Bronze Powdercoat Finish, with Angle Indicators, 1/2" Coin Plug, & Hardware
KH25AZ	Kitty Hawk Mounting Arm, Mounts Directly to Square Poles, Bronze Powdercoat Finish
ALMAAZ	Pole Mounting Arm Adaptor, Fits 2 3/8" Arm, Includes Hardware, Bronze Powdercoat Finish
KH25YZ	Yoke, Stamped Heavy-Duty Steel, Bronze Powdercoat Finish
KHEHZ	Easy Hang Wall Bracket, Bronze Powdercoat Finish
ACCHSG1Z	Die Cast Accessory Housing for Installing Sensors or Other Lighting Control, Bronze Powdercoat Finish
PTSB1SZ	Single Pole Tenon Spoke Bracket
PTSB290SZ	Twin Pole Tenon Spoke Bracket, 90° Arms, Bronze Finish
PTSB2180SZ	Twin Pole Tenon Spoke Bracket, 180° Arms, Bronze Finish
PTSB390SZ*	Triple Pole Tenon Spoke Bracket, 90° Arms, Bronze Finish
PTSB3120SZ*	Triple Pole Tenon Spoke Bracket, 120° Arms, Bronze Finish
PTSB490SZ*	Quad Pole Tenon Spoke Bracket, 90° Arms, Bronze Finish
KH20RP	Round Pole Adapter. Fits 3" or 4" O.D. Round Poles, Bronze Finish
P18130	480VAC Twist Lock Photocell Receptacle
P18131	Twist Lock Non-Shorting (Open) Cap Disconnects Service to Fixture for Temporary or Permanent Disabling (Fixture Always Off). IP65, 480V Maximum.
P18132	Twist Lock Shorting Cap Provides Fixed Service to Fixture (Fixture Always on). IP65, Rated Load 7200w Tungsten.
P18140	110-120VAC Instant Twist Lock
P18142	110-277VAC Instant Twist Lock
P18150	120VAC Time Delay Twist Lock
P18152	277VAC Time Delay Twist Lock
3EBL1202774500	Provides 90 Minutes of Backup Power.

*Special order item. Lead time three weeks.

LD


EasyLED Series

Bentley EasyLED Small Kitty Hawk Area Light



FL73SFXZ
(Shown Mounted)

FL73BRZ
(Shown Mounted)



KH25GLP



KH25AZ



ALMAAZ



KH25YZ



KHEHZ



ACCHSG1Z



PTSB1SZ



PTSB290SZ



PTSB2180SZ



PTSB390SZ*



PTSB3120SZ*



PTSB490SZ*



KH20RP



P18130



P18131



P18132




P18140,
P18142




P18150,
P18152




3EBL1202774500




KH25QC1X112U5KC




KH25QF1X112U5KC




LM-79 Report Available.
DesignLights Consortium™ Qualified Luminaire.



LM-79 Report Available.
DesignLights Consortium™ Qualified Luminaire.



LM-79 Report Available.
DesignLights Consortium™ Qualified Luminaire.



LM-79 Report Available.
DesignLights Consortium™ Qualified Luminaire.



WAREHOUSE-LIGHTING.COM