LSS SERIES Commercial Lighting



Type:

LSS-2FT-25W-MCTP-BK

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)



LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas, etc.

Ideal choice for residential, commercial, and industrial lighting. Steady performance and long lifetime. Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below

-eatures

- High Lumen Efficiency
- Ceiling Mount or Suspended Mount

Technical Specifications

Electrical:

- Voltage: 120-277VAC 60Hz
- Wattage: 5W/17W/20W/25W
- Power Factor: >0.99
- Efficacy: 130 LPW

Mechanical:

- Black Finish
- High Lumen Efficiency Lumen
- Lens: Polycarbonate Frosted Lens, Shatter Resistant
- Rated life: 50,000 Hrs
- Ceiling Mount or Suspended Mount
- Operating Temperature: -4°F -122°F
- Housing: Cold-rolled Steel
- IP20, Indoor Use Only
- 5-Year Warranty

23 1/2"(L) x 2 3/5"(W) x 2 2/3"(H)

- Linkable (Optional Alignment Bracket Available)
- MCTP: Multi Color Temperature & Multi Power/Wattage (Selectable)

Lighting:

Dimmable: 0~10V Dimming

Customer Name: Project Name:

Note:

- Total Lumens: 3250LM Max.
- Color Temperatures: 3500K/ 4000K/ 5000K
- MCTP: Multi Color Temperature & Multi Power/ Wattage (Selectable)
- Color Rendering Index: $CRI \ge 80$
- Reduces Energy Consumption Up to 80% Compared to a Fluorescent Fixture

Applications:

- LED Strip Light is a cost-effective, energy-efficient lighting fixture for surface mount applications such as corridors, stairwells, public rooms, schools, hospitals utility areas. etc.
- Ideal for applications requiring fixtures with motion sensor or battery backup, see factory-installed options below
- Ideal for residential, commercial, and industrial lighting. Steady performance and long lifetime


Other Models:

- 25W | 3250LM | LSS-4FT-25W-MCT
- 32W | 4160LM | LSS-4FT-32W-MCT

46W | 5980LM | LSS-4FT-46W-MCT







Sample Ordering

Model	Size	Wattage	Color Temp. Ho	ousing
LSS	= 2FT =	25W		BK

25W

Accessories:

Blank = No Option For Accessories

LSS-CB2 = ALIGNMENT BRACKET

SCL-TBC-WN = T-BAR CLIP WITH SUSPENSION HOLE ON TOP. WING NUT AND WASHER INCL. SCL-GSY10 = HEAVY-DUTY ADJUSTABLE 1/16" 10FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY20 = HEAVY-DUTY ADJUSTABLE 1/16" 20FT. SUSPENSION KIT WITH Y-CONNECTOR & LOOP GRIPPER & HOOKS - 70 LBS. MAX LOAD (2 PER SET)

SCL-GSY110 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-GSY120 = ADJ. 20FT 1/16in SINGLE SUSPENSION CABLE WITH Y HOOK ENDS. LOOP GRIPPER ON TOP 70 LBS. MAX LOAD (ORDER 3 FOR 8FT.)

SCL-CSY1-6FT= ADJ. 6FT 1/16in SINGLE SUSPENSION 5in CANOPY SET WITH Y DOUBLE KEY-HOLE END CONNECTORS, NONPOWER SIDE

SCL-CSY1P-6FT = ADJ. 6FT 1/16in SINGLE SUSPENSION 5in CANOPY SET WITH Y DOUBLE KEY-HOLE END CONNECTORS, POWER SIDE WITH SJTW18/5 WHITE CORD

Factory-Installed Options:

Blank = No Option For Accessories

Biank = No Option For Accessories OPT-EM-FM1INT = INTERNAL EMERGENCY BACKUP BATTERY OPT-SEN-2US = ULTRASONIC BI-LEVEL DIMMING (REMOTE NOT NEEDED) OPT-HBC-125TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 125V OPT-HBC-277TL-WH = NEMA TWIST-LOCK PLUG 8FT, 15A, 277V OPT-HBC-125SB-WH = STRAIGHT BLADE PLUG 10FT, 15A,125V, 3-CONDUCTOR 18AWG WEC-3RC = OPTIONAL REMOTE OPT-FWH-63 = 6FT 3-WIRE WHIP OPT-FWH-65 = 6FT 5-WIRE WHIP

ACCESSORIES:

3250LM



FACTORY-INSTALLED OPTIONS:



SCL-GSY10



SCL-GSY20



OPT-HBC-125SB-BK

OPT-HBC-125TL-BK OPT-HBC-277TL-WH

WEC-3RC





SCL-CSY1-6FT SCL-CSY1P-6FT



OPT-EM-FM1INT OP INT

OPT-SEN-2US INTERNAL FOR ALL MODELS OPT-FWH-63 OPT-FWH-65

WESTGATE



+

2