




PROJECT NAME: _____ CATALOG NUMBER: _____
 NOTES: _____ FIXTURE SCHEDULE: _____

Mars 2 LED UFO High Bay



DESCRIPTION

The Mars 2 uses an advanced die-cast aluminum heat sink that provides excellent thermal transfer to extend component life. The fixture has a lifetime of 50000+ hours and can operate between -40°F to 122°F (-40°C to 50°C). The fixture is built ruggedly, with a polycarbonate lens and is IP65 rated for wet locations. The Fixture comes standard with ring for suspension mount. Optional fixed bracket mount available.



FEATURES:

- Wattage Available: 100W, 150W and 200W
- Voltage: AC100-277
- CCT: 5,000K
- CRI: >80
- Lifespan: 50000 hours
- Operating temperature: between -40°F to 122°F (-40°C to 50°C)
- Dimensions:
 - Height (without ring): 3 1/8" (78mm)
 - Height (including ring): 4 13/16" (121mm)
 - Diameter: 12 11/16" (322mm)
- 0-10V dimmable LED power supplies
- Mount option: hanging ring
- Manufacturer Warranty: 5 years
- Listings: cULus, IP65



Item	Wattage	Voltage	CCT	Lumens
HG-HL-100WLD-50K8023-M5BK	100	100-277V	5000	14000
HG-HL-150WLD-50K8023-M5BK	150			21000
HG-HL-200WLD-50K8023-M5BK	200			28000





Warehouse-Lighting.com
 2750 South 163rd St
 New Berlin, WI 53151


Warehouse-Lighting.com
 Phone: 888-454-4480
info@warehouse-lighting.com




Dimension:mm(inch)



The installation diagram



Steel ring




U-Bracket

Wiring Connection

Turn off the power, connect AC wire.

Dimmer connection (With dimmable driver.)

1. Compatible with 0-10v dimming.
2. Connect wires as below, purple wire is D+, gray wire is D-



3. Hang up the light.

*Installation Note- In non-dimming application, cap purple and gray wires individually.



Warehouse-Lighting.com
2750 South 163rd St
New Berlin, WI 53151

Warehouse-Lighting.com
Phone: 888-454-4480
info@warehouse-lighting.com