

13.5T8/LED/48-835/DIM-BP 13.5 watt T8 LED; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1700 Lumens; Dimmable

### Features

- No ballast or external driver required
  Direct wire 120V line voltage\*
- Direct wire 120V line voltage
  Single ended wiring; Non-shunted socket
  All glass tube
  Long life: 50,000 hours
  cULus classified Damp location

- 5 year warrantyNSF Certified

\* Install only in non-shunted lampholders

Item Numbe	er	UPC	Voltage	Watts	Lamp Shape	Base	ANSI Base	Lan	Lamp Code			
S11921	045923119217		17 120	13.5	Т8	Medium Bi-P	in G13	13.5T8/LED/48-835/		35/DIM-BP		
Dimmable/Non- Sugg Dimmable			ested Dimmers	Finish	MOL Ir Inches		Initial Lumens	Average Rated Hours		Kelvin Temp		
Dimmable Cor			atible dimmers	Gloss White	48"	1.00"	1700	1700 50000		3500		
Color	CRI	Beam Spread Deg	Operating 1	emperature	Pack	CEC Status	D	LC ID:	RoHS Compliant			
Neutral White	82	220	-20C (-4F) to of +45C	a maximum (+113F)	10	Lawful for sale i California	n PLV12B <sup>2</sup> DLC Sea	Yes		Yes		
UL or	ETL L	isted		UL Classification						Warranty		
Yes			cUI	us Classified	l - Damp	Location Rated	5 Year Limited					



Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027





13.5T8/LED/48-840/DIM-BP 13.5 watt T8 LED; 4000K; Medium Bi Pin base; 50000 Average rated hours; 1800 Lumens; Dimmable

### Features

- No ballast or external driver required
  Direct wire 120V line voltage\*
- Direct wire 120V line voltage
  Single ended wiring; Non-shunted socket
  All glass tube
  Long life: 50,000 hours
  cULus classified Damp location

- 5 year warrantyNSF Certified

\* Install only in non-shunted lampholders

Item Numb	ber	UPC		Voltage	Watts	Lamp Shape		Base	ANSI Base	Lamp Code		ode		
S11922	S11922 0459231192		224	120	13.5	T8		Medium Bi-Pir	G13	13.5T8/LED/48-84		40/DIM-BP		
Dimmable/Non- Suç Dimmable			ggesteo	d Dimmers	Finish	MOL In Inches		MOD In Inches	Initial Lumens	Average Rated Hours		Kelvin Temp		
Dimmable Cor			e dimmers_ 1922	Gloss White	48''		1.00''	1800 50000			4000			
Color	CRI	Beam Spread De	g O	perating Ten	nperature	Pack		CEC Status	DI	DLC ID:		RoHS Compliant		
Warm White	82	220	-200	C (-4F) to a m +45C (+1		10	La	awful for sale in California	PLV12B1 DLC Sea	12B1YBIYP <u>Search</u>		Yes		Yes
UL o	r ETL	Listed		UL Classification						Warranty				
Yes				cULu	s Classified	- Damp	Loc	cation Rated		5 Year Limited				



Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027





13.5T8/LED/48-840/DIM-BP 13.5 watt T8 LED; 5000K; Medium Bi Pin base; 50000 Average rated hours; 1800 Lumens; Dimmable

### Features

- No ballast or external driver required
  Direct wire 120V line voltage\*
- Direct wire 120V line voltage
  Single ended wiring; Non-shunted socket
  All glass tube
  Long life: 50,000 hours
  cULus classified Damp location

- 5 year warrantyNSF Certified

\* Install only in non-shunted lampholders

Item Numb	ber	UPC		Voltage	Watts	Lamp Shape	÷	Base	ANSI Base	Lamp Code		de		
S11923	S11923 0459231192		231	120	13.5	T8		Medium Bi-Pin G13		13.5T8/LED/48-84		40/DIM-BP		
Dimmable/Non- Sug Dimmable			ggesteo	d Dimmers	Finish	MOL In Inches		MOD In Inches	Initial Lumens	Average Rated Hours		Kelvin Temp		
Dimmable Cor			<u>e dimmers</u> 1 <u>1923</u>	Gloss White	48''		1.00"	1800	1800 50000		5000			
Color	CRI	Beam Spread De	g O	perating Ten	nperature	Pack		CEC Status	DI	DLC ID:		RoHS Compliant		
Warm White	82	220	-200	C (-4F) to a m +45C (+1		10	La	awful for sale in California	PLV12B1 DLC Sea	I2B1YBIYP <u>Search</u>		Yes		Yes
UL o	r ETL	Listed		UL Classification						Warranty				
Yes				cULu	s Classified	- Damp	Loc	cation Rated		5 Year Limited				



Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027





13.5T8/LED/48-830/DIM-BP 13.5 watt T8 LED; 3000K; Medium Bi Pin base; 50000 Average rated hours; 1700 Lumens; Dimmable

### Features

- No ballast or external driver required
  Direct wire 120V line voltage\*
- Direct wire 120V line voltage
  Single ended wiring; Non-shunted socket
  All glass tube
  Long life: 50,000 hours
  cULus classified Damp location

- 5 year warrantyNSF Certified

\* Install only in non-shunted lampholders

Item Numb	ber	UP	C	Voltage	Watts	Lamp Shape		Base	ANSI Base	Lamp Code		de		
S11920	04592311920		19200	120	13.5	Т8		Medium Bi-Pir	G13	13.5T8/LED/48-83		30/DIM-BP		
Dimmable/Non- Suç Dimmable			Sugges	sted Dimmers	Finish	MOL In Inches		MOD In Inches	Initial Lumens	Average Rated Hours		Kelvin Temp		
Dim	Dimmable Cor			tible dimmers S11920	Gloss White	48''		1.00"	1700	1700 50000		3000		
Color	CRI	Beam Spread I		Operating Terr	perature	Pack		CEC Status	DI	DLC ID:		RoHS Compliant		
Warm White	82	220	-2	20C (-4F) to a m +45C (+11		10	La	wful for sale in California	PLV12B1 DLC Sea			Yes		Yes
UL o	r ETL I	Listed		UL Classification						Warranty				
Yes				cULu	s Classified	- Damp	Loc	cation Rated	5 Year Limited					



Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

