

S16406

24T8/LED/HO-SIGN/60-840/BP 24W T8 LED; 4000K; 3100 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

Features

- Base rotates 90° for easy installation
 Direct wire 120-277V line voltage*
 NSF Approved
 No ballast or external driver required



| Item N | Item Number UPC | | | | Voltage | | Watt | ts | Operating Frequency | | | Lamp Shape | | ase | ANSI Base | |
|--------|--|---|--|---------|--------------------|--|------|------|------------------------|-----------|----------------------------------|------------------------|-----------------------------------|----------------|---------------------|--|
| S10 | S16406 045923164 | | | 064 | 120-277 | | 24 | | 50/60 |)Hz | Т8 | | Recessed Double Contact HO/VHO | | R17d | |
| | Lamp Code | | | | sh MOL I Inche | | | | OD In nches | Initial I | _umens | Average Rated Hours | | Kelvin Temp | Color | |
| 24T | 24T8/LED/HO-SIGN/60- 840/BP | | | | - Frosted | | " | | 1.00" | 3100 | | 50000 | | 4000 | Cool White | |
| CRI | Beam S De | | Ope | erating | rating Temperature | | | Pack | Packag | е Туре | CEC | CEC Status | | 6 Compliant | UL or ETL Listed | |
| 83 | 33 | 0 | -40C (-40F) to a maximum +45C (+113F) | | | | | 10 | Sleeve | | Lawful for sale in California | | | Yes | Yes | |
| | UL Classification | | | | | | | | | | | | | Warranty | | |
| | cULus Classified - Damp Location Rated | | | | | | | | | | | | | 5 Year Limited | | |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051



S16407

24T8/LED/HO-SIGN/60-865/BP 24W T8 LED; 6500K; 3100 Lumens; 120-277V; Type B; Single Ended; Ballast Bypass

Features

- Base rotates 90° for easy installation
 Direct wire 120-277V line voltage*
 NSF Approved
 No ballast or external driver required



S16407

| Item Number L | | | UPC | voltage | | Wat | ts | Opera Frequ | 0 | Lamp Shape | | Base | | ANSI Base | | |
|---------------|--|--------------------------------------|--|-------------|-----------------|-------|----|----------------|---------------|----------------|----------------------------------|---------|-----------------------------------|---------------------|-------|--|
| S10 | S16407 04592 | | | 4071 120-27 | | 0-277 | 24 | Ļ | 50/60 | OHz | Т8 | | Recessed Double Contact HO/VHO | | R17d | |
| Lamp Code | | | | Finis | ish MOL Inch | | | | DD In ches | Initial Lumens | | | age Rated Hours | Kelvin Temp | Color | |
| 24T | 8/LED/H 865/ | V/60- | /60- Frosted | | 60' |)'' | | .00" | 3100 | | 50000 | | 6500 | Daylight | | |
| CRI | | ım Spread Operating Temperatu Deg | | | | | | Pack | Packag | CEC Status | | is Rol- | IS Compliant | UL or ETL Listed | | |
| 83 | 33 | 0 | -40C (-40F) to a maximum +45C (+113F) | | | | | 10 | Sleeve | | Lawful for sale in California | | • | Yes | Yes | |
| | UL Classification | | | | | | | | | | | | | Warranty | | |
| | cULus Classified - Damp Location Rated | | | | | | | | | | | | 5 Year Limited | | | |



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051