



S29926

12T8/LED/36-830/BP 120-277V
 12W T8 LED; Medium bi-pin base; 3000K; 50000 Average
 rated hours; 1400 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29926

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29926	045923299261	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-830/BP 120-277V	Non-Dimmable	White	36"	1.00"	1400	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
3000	Soft White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification		Warranty	
PL2P0M8SI8W4 DLC Search		Yes	Yes	cULus Classified - Damp Location Rated		5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S29927

12T8/LED/36-835/BP 120-277V
 12W T8 LED; Medium bi-pin base; 3500K; 50000 Average
 rated hours; 1400 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29927

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29927	045923299278	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-835/BP 120-277V	Non-Dimmable	White	36"	1.00"	1400	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
3500	Neutral White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification	Warranty		
PLZCLRCISTTC DLC Search		Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited		



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S29928

12T8/LED/36-840/BP 120-277V
 12W T8 LED; Medium bi-pin base; 4000K; 50000 Average
 rated hours; 1450 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29928

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29928	045923299285	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-840/BP 120-277V	Non-Dimmable	White	36"	1.00"	1450	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
4000	Cool White	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification		Warranty	
PLT50YQ026TP DLC Search		Yes	Yes	cULus Classified - Damp Location Rated		5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S29929

12T8/LED/36-850/BP 120-277V
 12W T8 LED; Medium bi-pin base; 5000K; 50000 Average
 rated hours; 1450 Lumens; Type B; Ballast Bypass; Double
 Ended Wiring

Features

- All glass tube
- Approved for use with tube guards
- Direct wire 120-277V line voltage*
- NSF Approved
- No ballast or external driver required
- Built-in shock resistant circuit - (not hot until both ends are installed)



S29929

*Existing wiring to both sockets can remain in place

*Will work on both shunted or non-shunted sockets

Item Number	UPC	Voltage	Watts	Operating Frequency	Fluorescent Equivalent	Lamp Shape	Base
S29929	045923299292	120-277	12	50/60Hz	25W	T8	Medium Bi-Pin
ANSI Base	Lamp Code	Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours
G13	12T8/LED/36-850/BP 120-277V	Non-Dimmable	White	36"	1.00"	1450	50000
Kelvin Temp	Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status
5000	Natural Light	82	210	-20C (-4F) to a maximum of +45C (+113F)	25	Box	Lawful for sale in California
DLC ID:		RoHS Compliant	UL or ETL Listed	UL Classification	Warranty		
PLCM6AAFCP4G DLC Search		Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited		



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

