

S39672

36W/LED/HID/2700K/100-277V/E26 36 watt LED HID Replacement; 2700K; Medium base; 100-277 volts

Features

- High Lumen Omni-directional LED for Industrial / Commercial applications
- Replaces HID, CFL, and Incandescent
 Ballast by-pass Direct wire only 100V 277V
- UL approved for totally enclosed fixtures
 Damp location IP64 rated
- For outdoor & indoor use
- Base up, base down or horizontal operation
- Emits no UV light / Contains no mercury (Hg)
- 5 year limited warranty
- cÚLus listed

Additional Technical Specifications

- Power Factor >0.9
- Operating temperature range -20°C to 65°C
- Operating Frequency 50-60Hz
- Working Voltage AC90-305V
- Built in Surge Protection: 4KV

Shatter resistant materials, acceptable for use in food prep areas

Minimum Compartment Size							
Length	Width	Depth					
6 inch	6 inch	8.5 inch					

Optional Accessories

- In-line surge protector 80-929
- Mog to med socket reducer (rated up to 600V) 92-410



S39672

Item	Product	UPC	Input	Watts	Operating	Incandescent	Fluorescent
Number	Line	UFC	Voltage	vvalis	Frequency	Equivalent	Equivalent

S39672	2	Hi-Pro	04	45923	306723	100 -	277	36	5	0/60Hz	200W			55W	
HID Equi	valent	Bas	e i	NSI ase		Lam	o Cod	е		Dimmable Dimma		Finish	MOL I Inche		DD In Iches
150V	V	Mediu	um E	26	36W/LI	ED/HID/27	00K/1	00-277V/	E26	Non-Dim	nable	White	7-11/3	2" 3-1	11/32"
Initial Lumen		verage Hou	Rated		lvin mp	Color	CRI	Bear Spread		Burning	Position	C	Operating	Tempera	ature
4680		500	00	27	00	Warm White	80	300)	Up, Down, or Horizont Operation Only		tal -20	. ,	(-4F) to a maximum of +65C (+149F)	
Pack	Pack Typ	•	CEC Status		tus	Material RoHS Compliant			UL or ETL Listed	UL Classification		Warr	anty		
12	Bo	х	Lawful Ca	for sa		Aluminu	m	Yes		Yes		us - Damp Location Rated		<u>5 Year I</u>	Limited



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



@2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051