



# S8690

13T5/LED/46-835/BP/HE/120-277V  
13W T5 LED; Miniature bi-pin base; 3500K; 50000 Average  
rated hours; 1600 Lumens; 120-277V; Type B; Ballast Bypass;  
Single Ended Wiring

## Features

- No ballast or external driver required
- All glass tube
- PETa€shatterproof coated
- NSF Approved



S8690

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S8690	045923086908	120-277	13	50/60Hz	T5	Miniature Bi-Pin	G5

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
13T5/LED/46-835/BP/HE/120-277V	Frosted	48"	0.88"	1600	50000	3500	Neutral White

CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PL8VVDCTNIUW <a href="#">DLC Search</a>	Yes	Yes

UL Classification						Warranty	
cULus Classified - Damp Location Rated						<a href="#">5 Year Limited</a>	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051



# S8691

13T5/LED/46-840/BP/HE/120-277V  
13W T5 LED; Miniature bi-pin base; 4000K; 50000 Average  
rated hours; 1650 Lumens; 120-277V; Type B; Ballast Bypass;  
Single Ended Wiring

## Features

- No ballast or external driver required
- All glass tube
- PETa€shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8691

Item Number	UPC	Voltage	Watts	Lamp Shape	Base	ANSI Base	Lamp Code	
S8691	045923086915	120-277	13	T5	Miniature Bi-Pin	G5	13T5/LED/46-840/BP/HE/120-277V	
Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color	CRI	
Frosted	48"	0.88"	1650	50000	4000	Cool White	83	
Beam Spread Deg	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed	UL Classification	Warranty	
240	25	Lawful for sale in California	PLJKLU33P9OA <a href="#">DLC Search</a>	Yes	Yes	cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>	



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027





# S8692

13T5/LED/46-850/BP/HE/120-277V  
13W T5 LED; Miniature bi-pin base; 5000K; 50000 Average  
rated hours; 1700 Lumens; 120-277V; Type B; Ballast Bypass;  
Single Ended Wiring

## Features

- No ballast or external driver required
- All glass tube
- PETa€shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8692

Item Number	UPC	Voltage	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base
S8692	045923086922	120-277	13	50/60Hz	T5	Miniature Bi-Pin	G5

Lamp Code	Finish	MOL In Inches	MOD In Inches	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
13T5/LED/46-850/BP/HE/120-277V	Frosted	48"	0.88"	1700	50000	5000	Natural Light

CRI	Beam Spread Deg	Operating Temperature	Pack	CEC Status	DLC ID:	RoHS Compliant	UL or ETL Listed
83	240	-20C (-4F) to a maximum of +45C (+113F)	25	Lawful for sale in California	PL1ES1XSI0M3 <a href="#">DLC Search</a>	Yes	Yes

UL Classification	Warranty
cULus Classified - Damp Location Rated	<a href="#">5 Year Limited</a>



National Toll-Free:  
800.43.SATCO  
(800.437.2826)  
[www.satco.com](http://www.satco.com)

Distribution Centers:  
New York, Florida, Texas,  
Washington, California,  
Puerto Rico

Corporate Offices:  
110 Heartland Blvd.,  
Brentwood, NY 11717  
800.437.2826 631.243.2022  
Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051