

## S8696

16T5/LED/36-835/BP/HO/120-277V 16W T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1800 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

### **Features**

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8696

Item	Number	r UPC		Voltage		Watts	Operat	ing Frequency	Lamp Shape	Base	ANSI Base	
S	S8696 0459230869		960	120-277		16		50/60Hz	T5	Miniature Bi-Pin	G5	
	Lamp Code			MO Inc	L In hes		DD In ches	Initial Lumens	Average Rat Hours	ed Kelvin Temp	Color	
16T5/	16T5/LED/36-835/BP/HO/120- 277V			3	6"	C	.88"	1800	50000	3500	Neutral White	
CRI	Beam Spread De	Operating Temperature		iture F	ack	CE	C Status	RoHS Complia	UL or E <sup>-</sup> int Listed	i – III Class	UL Classification	
83	240	-20C (-4F) to a maximum of +45C (+113F)			25		l for sale alifornia	e in Yes	Yes		cULus Classified - Damp Location Rated	
	Warranty											
	<u>5 Year Limited</u>											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027





## S8697

16T5/LED/36-840/BP/HO/120-277V 16W T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 1850 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

### **Features**

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8697

Item	Number	UPC		Voltage	Wa	tts Operating	Operating Frequency		Base	ANSI Base	
S	S8697 04592308697			120-277	16	50/	50/60Hz		Miniature Bi-Pin	G5	
	Lamp Code			MOL Inch		MOD In Inches	Initial Lumen	Average Ra s Hours	ted Kelvin Temp	Color	
16T5/	16T5/LED/36-840/BP/HO/120- 277V			36	'	0.88"	1850	50000	4000	Cool White	
CRI	Beam Spread De	Deg Operating Temperature			ck	CEC Status	RoHS Complia	UL or ET nt Listed	L UL Class	ification	
83	240	-20C (-4F) of +45		La	awful for sale in California	Yes	Yes	cULus Classif Location			
	Warranty										
	<u>5 Year Limited</u>										



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027





# S8698

16T5/LED/36-850/BP/HO/120-277V 16W T5 LED; Miniature bi-pin base; 5000K; 50000 Average rated hours; 1900 Lumens; 120-277V; Type B; Ballast Bypass; Single Ended Wiring

### Features

- No ballast or external driver required
- All glass tube
- PETâ€"shatterproof coated
- NSF Approved
- Single ended wiring; Non-shunted socket



S8698

Item	Number	r UPC		Voltage	١	Watts	Operati	ng Frequency	Lamp Shape	Base	ANSI Base	
S	S8698 0459230869		984	120-277		16 5		0/60Hz	T5	Miniature Bi-Pir	n G5	
	Lamp Code			MOI Incl			OD In nches	Initial Lumens	Average Rat Hours	ed Kelvin Temp	Color	
16T5/	16T5/LED/36-850/BP/HO/120- 277V			36	36"		).88"	1900	50000	5000	Natural Light	
CRI	Beam Spread De	Operating Temperature		iture P	ack	CE	EC Status RoHS		UL or E1	T III Clas	sification	
83	240	-20C (-4F) to a maximum of +45C (+113F)			25		I for sale in Yes		Yes		cULus Classified - Damp Location Rated	
	Warranty											
	<u>5 Year Limited</u>											



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027

