



S9930

15T8U6/LED/22.5-830/BP
 15W T8 U-Bend LED; Medium bi-pin base; 3000K; 50000
 Average rated hours; 1700 Lumens; Type B; Ballast Bypass;
 Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

S9930

* Install only in non-shunted lampholders

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base	Lamp Code
S9930	045923099304	15	50/60Hz	T8	Medium Bi-Pin	2G13	15T8U6/LED/22.5-830/BP
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp
Non-Dimmable	White	22.5"	7.00"	6"	1700	50000	3000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Warm White	82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	PJM4D71J DLC Search
RoHS Compliant	UL or ETL Listed	UL Classification	Warranty				
Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited				



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S9931

15T8U6/LED/22.5-835/BP
 15W T8 U-Bend LED; Medium bi-pin base; 3500K; 50000
 Average rated hours; 1700 Lumens; Type B; Ballast Bypass;
 Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

S9931

* Install only in non-shunted lampholders

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	Lamp Code	Dimmable/Non-Dimmable
S9931	045923099311	15	50/60Hz	T8	Medium Bi-Pin	15T8U6/LED/22.5-835/BP	Non-Dimmable

Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
White	22.5"	7.00"	6"	1700	50000	3500	Neutral White

CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:	RoHS Compliant
82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	P5DE5AYV DLC Search	Yes

UL or ETL Listed	UL Classification	Warranty
Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S9932

15T8U6/LED/22.5-840/BP
 15W T8 U-Bend LED; Medium bi-pin base; 4000K; 50000
 Average rated hours; 1800 Lumens; Type B; Ballast Bypass;
 Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

S9932

* Install only in non-shunted lampholders

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base	Lamp Code
S9932	045923099328	15	50/60Hz	T8	Medium Bi-Pin	2G13	15T8U6/LED/22.5-840/BP

Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp
Non-Dimmable	White	22.5"	7.00"	6"	1800	50000	4000

Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Cool White	82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	PH3SCEZH DLC Search

RoHS Compliant	UL or ETL Listed	UL Classification	Warranty
Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027





S9933

15T8U6/LED/22.5-850/BP
 15W T8 U-Bend LED; Medium bi-pin base; 5000K; 50000
 Average rated hours; 1800 Lumens; Type B; Ballast Bypass;
 Single Ended Wiring



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

S9933

* Install only in non-shunted lampholders

Item Number	UPC	Watts	Operating Frequency	Lamp Shape	Base	ANSI Base	Lamp Code
S9933	045923099335	15	50/60Hz	T8	Medium Bi-Pin	2G13	15T8U6/LED/22.5-850/BP
Dimmable/Non-Dimmable	Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp
Non-Dimmable	White	22.5"	7.00"	6"	1800	50000	5000
Color	CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	CEC Status	DLC ID:
Natural Light	82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	Lawful for sale in California	PR2J7GTN DLC Search
RoHS Compliant	UL or ETL Listed	UL Classification	Warranty				
Yes	Yes	cULus Classified - Damp Location Rated	5 Year Limited				



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

