

PROJECT NAME:		CATALOG NUMBER:
NOTES:	FIXTLIRE	SCHEDIII E.



The LED Shoebox Light series can be used in outdoor lighting (wet location certified). Excellent for parking lots, buildings, courtyards, industrial areas, sidewalks, schools and many other applications.

FEATURES:

- Lumileds LED: High lumen efficiency and long working life
- High efficiency LED Driver
- Input voltage AC120-277V
- High quality die cast aluminum design for excellent heat dissipation
- Optics designed to improve the light utilization and evenness
- Dimensions: L 24" x W 11.13" x H 6.3"
- Weight: 16.6 lbs
- DLC Partner: Wisdom
 - DLC ID#: P4PTJCKZ

OPTIONAL MOUNTING BRACKETS:











Warehouse-Lighting.com 2750 South 163rd St New Berlin, WI 53151



Technical Parameters Part Number: WSD-SB20W27-50K

Power	200W	Lighting Angle	Type II, III, IV,V
Input Voltage	AC120-277V	LED Brightness Decay	<5%/6000 hrs
PF	>0.95	Working Life	>50000 hrs
Driver Efficiency	>90%	Working Temperature	-30 - +45℃
Luminous Flux	27000 Lm	Storage Temperature	-40 -+80°C
Color Temperature	4000K/5000K	Protection Level	Wet Location/IP66
CRI	Ra>70	Cable	3 core, 18AWG

Photometry





