

# SFX SERIES OUTDOOR LIGHTING

SFX-G9-500W-45D-RGB  
LED STADIUM FLOOD LIGHTS

**WESTGATE**  
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!



Selection:




Customer Name: \_\_\_\_\_

Project Name: \_\_\_\_\_

Note: \_\_\_\_\_

Type: \_\_\_\_\_



20"(H) x 17 8/9"(W) x 16 4/5"(D)

Ideal for Stadium lighting, Sports fields, parking lots, docks, railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions

## Features

- Die-Cast Aluminum Housing With Powder Coat Finish (Black)
- LED: Lumileds Luxeon SMD 3535
- 7-year Warranty
- Lens: Prismatic Polycarbonate Lens

## Technical Specifications

### Electrical:

- Voltage: 120-277V AC 60Hz
- Wattage: 500W
- Power Factor: >0.90~0.97
- Efficacy: 150LPW

### Mechanical:

- Die-Cast Aluminum Housing with Powder Coat Finish (Black)
- In A DMX Lighting Setup, Lights Need To Be Connected With cables. The Cables Can Be "Daisy Chained" So That Each Light Can Plug Into The One Before It Instead Of All Lights Plugging Into The DMX Board Itself
- Cord Type: 3' SJTW 18/3 AWG Cable
- Effective Projected Area (EPA): 1.8 (sq. ft.)
- Operating Temperature: -40°F to 122°F
- IP Rating: IP66, Suitable for Wet Locations
- 7-year Warranty

### Lighting:

- Lens: Prismatic Polycarbonate Lens
- LED: Lumileds Luxeon SMD 3535
- Total lumens: 75000LM
- Color Temperatures: Red/Green/Blue
- Color Rendering Index: CRI ≥ 70
- Rated Life: 70,000 Hrs
- Beam Angle: 45°

### Applications:

- Stadium lighting, Sports fields, parking lots, docks, railway and container yards, Architectural lighting, Industrial and commercial exterior lighting, trade shows, exhibitions.




Phone: (877) 805-2252 | Fax: (877) 805-2252  
www.westgatemfg.com




WG-ZA-Z7-2Z

**Photometrics:** SFX-G9-500W-45D-RGB



BUG Rating: B5-U0-G2



600W 5000K, Area 80'x 80' Mounting Height: 9'

**Other Views:**



Shown with optional shroud



Front View



Back View

**Performance Table:** SFX-G9-500W-45D-RGB

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SFX-G9-500W-45D-RGB	600W	120~277V	75000LM	RGB	B5-U0-G2	150

**Sample Ordering**

Model	Style	Watt	Size	Color Temp.				
SFX	-	G9	-	500W	-	45D	-	RGB

**Accessories:**

Blank = No Option For Accessories  
 SFX-G9-SH1= SHROUD FOR G9 600W STADIUM LIG  
 SFX-G9-SF= SLIP FITTER, COMES WITH ITS OWN REPLACEMENT "U" BRACKET

**ACCESSORIES:**



SFX-G9-SH1



SFX-G9-SF

**Example:**

- SFX-G9-500W-45D-RGB
- SFX-G9-500W-45D-RGB  
SFX-G9-SH1

(FOR SFX 500W RGB FIXTURE 120-277V)

(FOR SFX 500W RGB FIXTURE 120-277V)  
(SHROUD FOR 500W)

