



WAREHOUSE-LIGHTING.COM



## Wall Pack

**LED-3120**

### APPLICATIONS

	Retails & Supermarkets
	Hotels & Restaurants
	Commercial Buildings
	Offices And Showrooms
	Schools & Colleges



### Product Description:

Easy access to photocell switch. Photocell is replaceable

Easy access to the control switch for a range of CCTs and wattages to choose from

Door Frame  
The door frame is designed with the installer in mind. It has a simple to use hinge access, allowing installers to be hands-free when entering electrical compartment. This saves time and money.

Emergency Backup Driver option

Integrated Heatsink  
Integrated cooling fin provides excellent thermal dissipation. This design allows the fixture to have extremely long lifetime hours.

Proprietary Optical Control  
Specifically designed lens for freedom of layout design without any restraint. These optics are engineered for maximum light output.

**Wattage Selectable**

**COLOR TUNABLE**  
3000K-5000K

### Product Description:

The LED-3120 is a powerful luminaire that has been designed to meet a wide variety of locations. With the various mounting options it can be used as a flood light or as an area light. With the LEDs mounted on the large heatsink, the fixture can maintain a high lumen output while keeping the LED modules at a cool temperature.

Optional Kelvin color\* with adder.

### Features:

- LISTING**  
UL and CUL listed for wet locations
- HOUSING**  
Heavy duty die-cast aluminum powder coating, corrosion resistant hardware
- FINISH**  
UV stabilized powder coated finish
- LENS**  
Heat and impact PC Lens
- OPTIONS**  
Wide / narrow distribution available with adder  
Finish - Bronze. Color option with adder

## Performance Data

Model NO.	System Watts	Lumens	LPW
LED-3120	60/80/110W	14169 lm**	130 lm/w
Lumen and Efficacy are based on the highest wattage at 5000K			

## Specification:

Example: LED-3120

Model No.	System Watts	Input Voltage	CRI	Color Temp	Distribution	Option	Finish	Starting Temp
						Accessories		
LED-3120	110=110W	UNV=120-277V	7=70+	40=4000 K 50=5000 K	T3=Type III T4=Type IV	PE=Photocontrol EM=Emergency Driver FAO=FAO Controller	BZ=Bronze	-40°C

\* Different LED Kelvin temperature available with 4-6 week lead time. Please call for a quote.

\*\* DISCLAIMER: This test report was produced in accordance with IES LM-79 photometric testing protocol for luminaires, using a single representative test fixture. Actual production units may vary from the values reported here by up to ±10%.

## Dimension:

