



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Square Beam Direct Series



This square shaped direct light fixture can add striking illumination to your space. The fixture consists of four 2 foot beams joined with a specially designed, illuminated L piece. It can be pendant or surfaced mounted.

Specifications

CRI	>80	Ratings and Certifications	cULus, Damp Location
Light Source	LED	Dimmable	0-10v dimming
Voltage	120-277	Beam Angle	Wide
Color Temperature	3000K / 3500K / 4000K / 5000K	Mounting Options	Suspended
Wattage	80W	Operating Temperature	-30°C to 40°C (-22°F to 104°F)
LPW	110	Lumens	8800
Housing	Extruded Aluminum	Finish	Black or White
Lifespan	54,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____


Order Information

Square 4' Beam			Example: SQ-BEAMLED2-80W-4CT-BK-G2		
Series	Light Direction	Wattage	Color Temperature	Finish	Generation
SQ-BEAMLED2	Blank Direct	80W	4CT 3000K/3500K/4000K/5000K	BK Black	G2
	DID Direct/Indirect	120W		WH White	

Dimensions

Item	Length	Width	Height	Weight
SQ-BEAMLED2-80W-4CT-BK-G2	29.69"	2.75"	3.38"	21.12 lbs
SQ-BEAMLED2-80W-4CT-WH-G2	29.69"	2.75"	3.38"	21.12 lbs
SQ-BEAMLED2-DID-120W-4CT-BK-G2	29.69"	2.75"	3.38"	21.12 lbs
SQ-BEAMLED2-DID-120W-4CT-WH-G2	29.69"	2.75"	3.38"	21.12 lbs

L Connector



Item	Joint Type	Dimensions	Weight
BEAM-4CCT-L-CNTR-BK-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs
BEAM-4CCT-L-CNTR-WH-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs