SRL6 SERIES Commercial Lighting

SRL6-8FT-MCTP

SLOT RECESSED COMMERCIAL LINEAER LIGHTS, 6" WIDE


Multi Color Temperature (Selectable)



This indoor commercial LED Blacklit panel light is ideal for hotels, offices, retail outlets, restaurants, parking garages, storage rooms, conference rooms, education facilities, and more.



Customer Name:	
Project Name:	
Note:	Type:



95 3/4"(L) x 5 5/6"(H) x 2"(D)

Features

- Soft and Wide Light-Emitting
- 50,000 Hours Rated Life
- No Infrared Rays, No Ultraviolet Radiation, No Thermal Effect
- Earthquake Hooks and Suspension Hooks Pre-Installed
- No Flickering, No Humming, No RF Interference
- Multi Color Temperature & Multi Power (Selectable Switch on Back of Fixture)

Technical Specifications

Electrical:

Voltage: AC120V-277V 50/60Hz

Power Factor: >0.90Wattage: 40W/60W/80WEfficacy: 110 LPW

Fixture Operating Voltage: 36VDC

Rated Input Current (mA): 337/ 253/ 168mA

Total Harmonic Distortion: ≤ 20 %

Mechanical:

- White Finish
- Earthquake Hooks And Suspension Hooks Pre-installed
- External Driver Mounted On Top
- Operating Temperature: -68°F~104°F
- Surge Protector: 1KV, 2.5KV
- 5-Year Warranty

Lighting:

• Dimmable: 0~10V Dimming

Total Lumens: 8800LM Max.

Color Temperatures: 3500K/4000K/5000K

Multi CCT & Multi Power

(Selectable Switch On Back Of Fixture)Color Rendering Index: CRI ≥ 80

Beam Angle: 110°

Rated Life: 50,000 Hrs

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, storage room, conference room, education facilities and more.

Other Models:

• 20W | 2200LM | SRL6-2FT-MCTP • 40W | 4400LM | SRL6-4FT-MCTP











Photometrics: SRL6-8FT-MCTP





40 30 25 20 15 2fc 10 0.5fc 5 0.1fc 10 15 20 30 50 Simulation Based on 4000K Area 50'x 50' Mounting Height: 9'

BUD Rating: B2-U2-G1

Other Views:





Side View

Front View

Back View

Performance Table: SSRL6-8FT-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
SRL6-8FT-MCTP	40W 60W 80W	120~277V	2200LM 3300LM 4400LM	4400K/ 6600K/ 8800K	B2-U2-G1	110

Sample Ordering

Model

Size Watt/Color Temp.

SRL6

8FT

MCTP

Accessories:

Blank = No Option For Accessories WEC-2DLH-22 = DAYLIGHT HARVESTING

WEC-2CPDR-= MOTION SENSOR WEC-3RC = OPTIONAL REMOTE CONTROL

Factory-Installed Options:

Blank = No Option For Accessories

OPT-EM-SRL6-8FT = INTERNAL EMERGENCY BACKUP BATTERY

OPT-FWH-63= 6FT 3-WIRE WHIP OPT-FWH-65= 6FT 5-WIRE WHIP OPT-FWH-66= 6FT 6-WIRE WHIP

ACCESSORIES and MOUNTING KIT:







WEC-2CPDR-3

WEC-3RC

WEC-2DLH-22

FACTORY-INSTALLED OPTIONS:



OPT-EM-SRL6-8FT



OPT-FWH-65 OPT-FWH-66





