

Texas Fluorescents Reinvented

# SS213 SERIES Smart Sense Wall Mount



Our popular 213 series utilizes an integral ultrasonic occupancy sensor to sense motion within a space and automatically turns on lights even when the sensor has no direct line of sight to occupants. After the area is vacated and the time delay has elapsed, the sensors automatically turn the lights off. Ultrasonic detection operates by transmitting sound waves throughout an area and measuring the speed at which they return. Movement increases the return frequency, which triggers occupancy. Saylite's Ultrasonic smartsensors provide functions for testing, overriding the fixture "ON" and a 72 hour lamp burn-in ode. Fixture is 4200 lumens when the sensor is on and can either be off or have 50% of the lumens or 2100 lumens when no one is present. This is a great, economical choice for bi-level lighting in a confined space with the untrasonic sensor. The X1LED stairwell series utilize efficient LED T8 lamps that provide high lumen output with efficient energy savings. Since they don't require any ballast or driver the only component that will ever need changing is the LED T8 lamp. The lamps are warranted for five years. Unlike SS213 series that utilize LED arrays and drivers these fixtures have the flexibility to change wattage, lumens, and color temperature simply by changing the lamps without the need to call a licensed electrician.

#### LAMP

2 lamp positions

#### CONSTRUCTION

Housing is die-formed and embossed code 22 gauge steel. Standard finish is high reflectance baked white enamel; custom finishes are available as an option. Wiring knockouts are provided on back of housing. The clear, ribbed lens is fully captured by the end plate. End cap held in place with acorn nut.

- Optional internal divider separates up and down light. Optional front baffle restricts light to up and down only (no front light). Add dual ballasts for separate control of up and down light.
- Options include emergency ballasts, pull chain switches and convenience outlets
- · Contact factory for custom, compact fluorescents night light options

### MOUNTING

Direct wall mount

## **SIZE W x L x H in inches** 4.50H x 4.4W

Available in 24 1/4", 36 1/4" and 48 1/4" lengths



#### X1 LED

The most economical, practical and user friendly series of LED fixtures with the energy savings, quality of light, long life and hassle-free maintenance. X1 LED fixtures are UL Listed with the latest LED T8 Bypass lamps. Fixtures provide over 44% energy savings over comparable fluorescent fixtures utilizing less expensive fixtures than the fluorescent version (no ballast required) and have flexibility to change wattage and color temperature any time. Fixture performance will evolve over time with the evolution of the T8 LED lamp technology. Concerned about maintenance with an LED array and driver fixture, X1 LED solves that by utilizing a self contained LED lamp that fits into fixture just like a fluorescent lamp.

### Lamp Specifcations:

Our T8 LED lamps are available in 2 or 4 ft sizes in different wattage, lumens and color temperature options. Savegreen Lighting is a premier supplier of LED T8 lamps and makes a variety of Bypass T8 lamps to meet the needs of your special application. Options include more energy efficient 12W, 15W and 17W lamps with Premium 10 Year warranty as well as high output options up to 3500 lumens. Double ended LED T8 lamps are also available. See lamp options and specs at www.savegreenlighting.com.

### **Optional Dimming Options:**

The 4 FT lamps are available with two dimming options; Specially designed dimming lamps require an external driver that runs 1 or 2 lamps. So more than 2 lamps require multiple external drivers or Consult for Bypass Type B lamps that can be dimmed without any external driver and dim with standard 2 wire dimming. See dimming options and specs at www. saylite.com.

### **Emergency Options:**

The standard X1 LED Lamps require an inverter or an All-inone emergency kit that includes LED array, battery and driver. Dimmable T8 LED with external driver works with standard LED EM. For a 5 watt inverter that is similar to adding a 500 Lumen emergency in a conventional fluorescent fixture, add "INV5W" to the end of the item number. This will allow 5 watts of one lamp to work in emergency mode. Or add "EMKT12" to the end of the item number to get a 12W stand alone emergency kit in the fixture that comes with a driver, battery and small LED array that works in Emergency mode. See emergency options and specs at www.saylite.com.



#### Saylite, Texas Fluorescents Revisited 2055 Luna Rd. Suite 142 Carrollton, TX 75006 Depres 072 247 2171 Faire 072 247 0200

Phone: 972-247-3171 Fax: 972-247-0200 www.saylite.com email: sales@saylite.com

Catalog Number:	
Notes:	





# **Texas Fluorescents**

Reinvented

### **Ordering Options**

(Fixtures below include LED T8 Lamp LT8ABP48L18W2250LXXK. For Other Lamp Options See below and Replace LNXXX with short code below. Specifiy without Lamps by removing LNXXX)

ITEM NO.	DESCRIPTION		
SS213A232X1LN18W40	4ft. Wall 4500 Lumen 2x18W LED T8 4000K Lamps Included		
1 Light on Always, 1 Light on Sensor			

Change 40 to 35 or 50 for different Kelvin. Change Lamp Wattage to 15W on 2FT or 15W on 4FT

For 5W Emergency, Add INV5 at the End of Item Number for KTEMRGLED5500AC. See other options at www.saylite.com

For fixtures wired for double ended lamps, change X1 to X2 and see the Savegreen Lamps below for the proper Double Ended Lamp. For fixtures without lamps included, remove the "LNXXX" at the end of the item number and have X1 or X2 for Single or Double Ended wiring.

LN18W40 - Lamp Specification 50,000 Hour Life with 5 Year Warranty Beam Angle 140 Degree Aluminum Base and Aluminum Housing with Glass Cover Operating Temperature: - 20C to 50C Color Temperature: 3500K, 4000K, 5000K G13 Pins (Same as Fluorescent Linear T8 Bipin) AC100 – 277V without Ballast Single Ended or Double Ended Power (If not specified use X1 Single Ended Power)

# Savegreen T8 or T5 LED Lamp Options

To include one of these lamps in fixture, remove "LNXXX" and add Savegreen Inside code below.

(See www.savegreenlighting.com for specification sheets or more information on these lamp options.)

VERSION	SAVEGREEN INSIDE	SAVEGREEN ITEM NO.	
Popular	SGB15W35	LT8BG48L15W1740LXXK	]
Standard	SGS29W35	LT8BGC24L9W1050LXXK	]
Standard	SGS312W35	LT8BGC36L12W1200LXXK	]
Standard	SGS15W35	LT8BGC48L15W1740LXXK	]
Premium	SGP12W35	L10T8BGC48L12W1750LXXK	] 10-YEAR
Premium	SGP15W35	L10T8BGC48L15W2000LXXK	WARRANTY
Premium	SGP18W35	L10T8BGC48L18W2500LXXK	
High Output	SGH26W40	LT8BGC48L26W3500LXXK	]
Double Ended	SGD18W35	LT8BDGC48L18W2100LXXK	]
Т5НО	SGT525W40*	LT5BG46L25W3300LXXK	]
Magic	SGM18W35K	LT8ABP48L18W2250LXXK	]
Magic	SGM18W35K	LT8ABP48L15W1875LXXK	]
Magic	SGM215W35K	LT8ABP24L15W1875LXXK	]
Change 35 to 40 c	r 50 for different Kelvin.		-

or 50 for different Kelvin. \*For T5, CCT 40K and 50K available.



Saylite, Texas Fluorescents Revisited 2055 Luna Rd. Suite 142 Carrollton, TX 75006 Phone: 972-247-3171 Fax: 972-247-0200 www.saylite.com email: sales@saylite.com

Catalog	Number:
---------	---------

Notes: