



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Stairwell LED Series



WareLight's stairwell LED lights combine cutting-edge LED technology with sleek and modern designs. Our stairwell light is CCT and wattage selectable, available in 2-foot and 4-foot lengths and are designed to be wall mounted. Ideal for residential, commercial, and institutional settings, they are suitable for a wide range of applications. Illuminate hallways, corridors, stairwells, and entryways with confidence, knowing that our lights will provide reliable performance in any environment.

## Specifications

CRI	82	Ratings & Certifications	cULus, Damp Location
Light Source	Integrated LED	Beam Angle	Wide
Dimmable	0-10v	Linkable	Continuous Run Available
Color Temperature	Selectable 3500K - 4000K - 5000K	Mounting Options	Wall Mounted (mounting kit included)
Wattage	Selectable 10W-40W	Operating Temperature	-30 ~ 40 °C (-22°F to +104°F)
LPW	115/w	Lumens	1,150-4,600lm
Voltage	120-277v	Lens	Milky Lens
Finish	White	Warranty	5 Years





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Order Information

LED Corridor Light Series		Example: WL-SWLED2-20W-CWS-WH-MS			
Series	Length	Wattage	Color Temperature	Finish	Accessories*
<b>WL-SWLED</b>	<b>2</b> 2 Foot	<b>20W</b> 10W/15W/20W	<b>CWS</b> 35K/40K/50K	<b>WH</b> White	<b>MS</b> Motion Sensor
	<b>4</b> 4 Foot	<b>40W</b> 20W/30W/40W			<b>EM</b> Emergency Battery Backup

\*Accessories Sold Separately

**Motion Sensor (MS)**



**Emergency Battery Backup (EM)**



## Performance Chart

Model Number	Size	Wattage	Lumens	Efficacy	CRI
WL-SWLED2-20W-CWS-WH	2 FT	10W/15W/20W	1,150-2,320	115 LM/W	82
WL-SWLED4-40W-CWS-WH	4 FT	20W/30W/40W	2,320-4,600	115 LM/W	82

## Dimensions

Item	Length	Width	Height	Weight
WL-SWLED2-20W-CWS-WH	24.02"	3.66"	3.54"	lbs.
WL-SWLED4-40W-CWS-WH	48.03"	3.66"	3.54"	lbs.

