



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Saturn G2 Series



These high performing, high bay lights are an energy-efficient replacement for traditional HID fixtures with mounting heights ranging from 15' to 40' depending on wattage and application. These fixtures are instant on and give you the freedom to control the brightness with 0-10V dimming. They are widely used in warehouses, cold storage facilities, workshops, convention centers, retail stores, gymnasiums, factories, and other industrial and commercial indoor areas.

## Specifications – 200W

CRI	<80	Ratings and Certifications	UL, IP65, DLC Premium v5.1
Light Source	LED	Dimmable	0-10V
Voltage	120-277V	Beam Angle	110°
Color Temperature	5000K	Mounting Options	Hook, Pendant, Bracket
Wattage	200W	Operating Temperature	-40°C - +50°C (-40°F - +122°F)
LPW	185	Lumens	37,000
Housing	Die-cast Aluminum	Finish	Black
Product Weight	4.6 lbs.	Product Dimensions	11.8" x 11.8" x 5.1"
Shipping Weight	6.1 lbs.	Shipping Dimensions	13.8" x 13.8" x 8.0"
Lifespan	L70-50,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Order Information

Saturn Series			Example: WL-SIUFO-100W-50K-UNV-BK-G2		
Series	Wattage	CCT	Voltage	Color	Generation
WL-SIUFO	100W	5000K	UNV 120-277V	BK Black	G2
	150W				
	200W				
	240W				

## Accessories

### Mounting Bracket Black or White

WL-BT-BRT-PA-BK-G3 / WL-BT-BRT-PA-WH-G3



### Emergency Battery Backup

WL-LECV-UFO-40D-R-G3



### EM Remote

WL-BT-RC-EM



### Conduit Boxes

CondMT-BK / CondMT-WH



### Sensor Remote

WL-HD05R



## DLC Information

Item	DLC Version	DLC ID	Wattage	Lumens
WL-SIUFO-100W-50K-UNV-BK-G2	5.1 Premium	S-VQ9E08	104.4W	19,446
WL-SIUFO-150W-50K-UNV-BK-G2	5.1 Premium	S-8M50CZ	153.3W	28,640
WL-SIUFO-200W-50K-UNV-BK-G2	5.1 Premium	S-78AXSF	201.2W	37,493
WL-SIUFO-240W-50K-UNV-BK-G2	5.1 Premium	S-PE231C	243.1W	46,870



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Dimensions

Item	Height	Diameter	Weight
WL-SIUFO-100W-50K-UNV-BK-G2	4.52"	9.68"	3.13 lbs.
WL-SIUFO-150W-50K-UNV-BK-G2	4.72"	10.47"	3.93 lbs.
WL-SIUFO-200W-50K-UNV-BK-G2	5.07"	11.81"	4.59 lbs.
WL-SIUFO-240W-50K-UNV-BK-G2	5.39"	12.79"	5.56 lbs.

## Photometrics

Saturn 200W 5K 110° Optic

