



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Square Beam Direct/Indirect G2 Series



**This square shaped direct or direct/indirect (up/down) light fixture can add striking illumination to your space. The fixture consists of four 4 foot beams joined with a specially designed, illuminated L piece. It can be pendant or surfaced mounted.**

## Specifications

CRI	>80	Ratings and Certifications	cULus, Damp Location
Light Source	LED	Dimmable	0-10v dimming
Voltage	120-277	Beam Angle	Wide
Color Temperature	3000K / 3500K / 4000K / 5000K	Mounting Options	Suspended
Wattage	260W	Operating Temperature	-20°C to 40°C (-22°F to 104°F)
LPW	Black Housing 105 White Housing 115	Lumens	Black Housing 27,300 White Housing 29,900
Housing	Extruded Aluminum	Finish	Black or White
Product Weight	26.44 lbs.	Shipping Weight	30.88 lbs.
Lifespan	54,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_



## Order Information

Square 4' Beam			Example: SQ-BEAMLED4-160W-4CT-BK-G2		
Series	Light Direction	Wattage	Color Temperature	Finish	Generation
SQ-BEAMLED4	<b>Blank</b> Direct	<b>160W</b>	3000K/3500K/4000K/5000K	<b>BK</b> Black	G2
	<b>DID</b> Direct/Indirect	<b>240W</b>		<b>WH</b> White	

## Dimensions

Item	Length	Width	Height	Weight
SQ-BEAMLED4-160W-4CT-BK-G2	57.47"	2.75"	3.38"	26.44 lbs
SQ-BEAMLED4-160W-4CT-WH-G2	57.47"	2.75"	3.38"	26.44 lbs
SQ-BEAMLED4-DID-260W-4CT-BK-G2	57.47"	2.75"	3.38"	26.44 lbs
SQ-BEAMLED4-DID-260W-4CT-WH-G2	57.47"	2.75"	3.38"	26.44 lbs

## L Connector



Item	Joint Type	Dimensions	Weight
BEAM-4CCT-L-CNTR-BK-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs
BEAM-4CCT-L-CNTR-WH-G2	L	5.79" L x 5.79" W x 3.35" H	1.1 lbs