

# Strip Lights

# Residential and Commercial Strip Lights



**4' Direct Wire High Lumen**  
33w 4900 Lumen  
5000K 120-277V  
54583361

**8' Linkable High Lumen**  
90w 9000 Lumen  
4000K 120V  
54599142

**4' Direct Wire/Plug-In**  
17w 1800 Lumen  
4000K 120V  
54261143

## ETI<sup>®</sup> ADVANTAGE



- ✓ Linkable models can be tandem mounted connecting up to 10 fixtures
- ✓ Available in direct wire and plug-in models

### STRIP LIGHT MODELS

### LIGHTING CONTROL AND SAFETY



90600121 • Multi-Volt Occupancy Sensor with daylight sensor

70101101 • Universal wattage BBU

90600143 • Universal wattage BBU

70112201 • 25w Emergency LED Driver/BBU

70112202 • 25w Emergency LED Driver/BBU

70114401 • 40w Emergency LED Driver/BBU

70114401 • 40w Emergency LED Driver/BBU

### Features & Specifications

- Durable impact resistant lens • Temp rating -4°F-113°F • 120V-277V or 120V\* • >80 CRI
- L70 >50,000 • 5 year limited warranty

### DIRECT WIRE

**2' Direct Wire**  
17w 1800 Lumen  
4000K 120-277V  
ST-2-18-840-MV-N  
54260144

**4' Direct Wire**  
34w 3600 Lumen  
4000K 120-277V  
ST-4-36-840-MV-N  
54283144

**4' High Lumen, Compatible with Battery Back-Up**  
33w 4900 Lumen  
5000K 120-277V  
ST-4-33-850-MV-N-EM  
54583361

### LINKABLE

**2' Linkable\* Direct Wire/Plug-In**  
8.5w 900 Lumen  
4000K 120V  
ST-2-9-840-SV-N  
54263143

**4' Linkable\* Direct Wire/Plug-In**  
17w 1800 Lumen  
4000K 120V  
ST-4-18-840-SV-N  
54261143

**4' Linkable/Direct Wire High Lumen 0-10V Dimmable**  
45w 5000 Lumen  
5000K 120-277V  
ST-4-45-850-MV-D  
54573161

**8' Linkable\* High Lumen**  
90w 9000 Lumen  
4000K 120V  
ST-8-90-840-SV-N  
54599142

## PART NUMBER GUIDE

CATEGORY	SIZE	LUMENS	CRI/CCT	VOLTAGE	DIMMING	OPTION
ST						

## PRODUCT/SKU DETAILS

### GENERAL SPECIFICATIONS:

<b>Voltage</b>	120VAC*/120-277VAC	<b>Frequency</b>	50/60 Hz.	<b>CRI</b>	80
<b>Power Factor</b>	>.90	<b>THD</b>	<20%	<b>Rating</b>	cULus Damp
<b>Temperature</b>	-4°F to +113°F	<b>Rated Life</b>	50,000 hrs.	<b>Warranty</b>	5 Year Limited

## ORDERING GUIDE

Part #	Model #	Description	Replaces	LED Watts	Lumens	LPW	CCT	Product Dimensions	CRI	Input Voltage	Case Pack
ST-2-18-840-MV-N	54260144	2' Strip Light, Direct Wire	32w T8	17w	1,800	106	4000K	24 x 2.2 x 2.7 in.	>80	120-277V	6
ST-4-36-840-MV-N	54283144	4' Strip Light, Direct Wire	2 x 32w T8	34w	3,600	106	4000K	48 x 2.2 x 2.7 in.	>80	120-277V	4
ST-4-45-850-MV-D	54573161	4' Linkable High Lumen Output Strip Light - 0-10V Dimmable	3 x 32w T8	45w	5,000	111	5000K	48 x 1.8 x 2.2 in.	80	120-277V	6
ST-2-9-840-SV-N*	54263143	2' Linkable Strip Light, Direct Wire or Plug-In	20w T8	8.5w	900	106	4000K	24 x 1.6 x 2.3 in.	>80	120V	6
ST-4-18-840-SV-N*	54261143	4' Linkable Strip Light, Direct Wire or Plug-In	2 x 32w T8	17w	1,800	106	4000K	48 x 1.6 x 2.3 in.	>80	120V	4
ST-4-33-850-MV-N-EM	54583361	4' High Lumen Output Strip Light, Compatible with Battery Back-Up	3 x 32w T8	33w	4,900	148	5000K	48 x 1.8 x 2.2 in.	80	120-277V	6
ST-8-90-840-SV-N*	54599142	8' Linkable Strip Light (ENERGY STAR®)	400w	90w	9,000	100	4000K	95.5 x 4.1 x 2.4 in.	80	120V	2


### Accessories

N/A	90600121	External Motion Sensor - Compatible with 54573161, 54599142, 54263143, 54283144, 54261143, 54260144	N/A	N/A	N/A	N/A	N/A	2.8 x 2.8 in.	N/A	120-277V	4
BLD-AM08N	70101101	Universal Wattage BBU for Non-Isolated Driver - Compatible with 54573161, 54583361	N/A	8w (Max)	N/A	N/A	N/A	2.0 x 1.8 x 9.3 in.	N/A	100-277VAC	1
EMJ-0825	90600143	Battery Back-Up - Compatible with 54583361	N/A	25w (Max)	N/A	N/A	N/A	2.2 x 10.1 x 9.9 in.	N/A	120-277V	6
EMUFO-25170-YY	70112201	Emergency LED Driver/BBU, Hanging/Round - Compatible with 54263143, 54261143, 54260144	N/A	25w	N/A	N/A	N/A	11 x 3.9 x 1.5 in.	N/A	100-347V	4
EMA-25FY-170	70112202	Emergency LED Driver/BBU - Compatible with 54263143, 54261143, 54260144	N/A	25w	N/A	N/A	N/A	12.4 x 2.3 x 1.5 in.	N/A	100-347V	10
EMUFO-40170-YY	70114401	Emergency LED Driver/BBU, Hanging/Round - Compatible with 54283144, 54573161, 54583361	N/A	40w	N/A	N/A	N/A	11 x 3.9 x 1.5 in.	N/A	100-347V	4
EMA-40FY-170	70114402	Emergency LED Driver/BBU - Compatible with 54283144, 54573161, 54583361	N/A	40w	N/A	N/A	N/A	12.4 x 2.3 x 1.5 in.	N/A	100-347V	10

# Strip Lights

Project:   
 Part Number:

## PART NUMBER GUIDE



## PRODUCT/SKU DETAILS

### GENERAL SPECIFICATIONS:

<b>Voltage</b>	120VAC*/120-277VAC	<b>Frequency</b>	50/60 Hz.	<b>CRI</b>	80
<b>Power Factor</b>	>.90	<b>THD</b>	<20%	<b>Rating</b>	cULus Damp
<b>Temperature</b>	-4°F to +113°F	<b>Rated Life</b>	50,000 hrs.	<b>Warranty</b>	5 Year Limited

## PACKAGING SPECIFICATIONS

Part #	Model #	UPC	UCC	Inner Carton Dimensions	Inner Carton Weight	Shipper/Master Carton Dimensions	Shipper/Master Carton Weight
ST-2-18-840-MV-N	54260144	849489002682	50849489002687	24.7 x 3.2 x 2.6 in.	1.7 lbs.	25.2 x 8.3 x 7.2 in.	12.1 lbs.
ST-4-36-840-MV-N	54283144	849489002675	50849489002670	48.8 x 3.15 x 2.56 in.	2.8 lbs.	49.2 x 6.9 x 6 in.	14.1 lbs.
ST-4-45-850-MV-D	54573161	849489002804	50849489002809	48.7 x 2.0 x 3.9 in.	3.3 lbs.	53.6 x 8.4 x 7.7 in.	22 lbs.
ST-2-9-840-SV-N	54263143	849489002606	50849489002601	24.7 x 2.8 x 2.0 in.	1.8 lbs.	26.79 x 7.64 x 8.67 in.	12.9 lbs.
ST-4-18-840-SV-N	54261143	849489002590	50849489002595	48.8 x 2.8 x 2.0 in.	3.2 lbs.	50.9 x 6.2 x 7.8 in.	14 lbs.
ST-4-33-850-MV-N-EM	54583361	849489002989	50849489002984	48.7 x 3.9 x 2.0 in.	5.6 lbs.	51 x 8.4 x 6.9 in.	25.5 lbs.
ST-8-90-840-SV-N	54599142	849489060132	50849489060137	97.1 x 5.4 x 3.6 in.	12.5 lbs.	97.6 x 9.5 x 7.2 in.	8.3 lbs.
<b>Accessories</b>							
N/A	90600121	849489009513	50849489009518	6.4 x 4.8 x 2.4 in.	1.1 lbs.	20.1 x 12.8 x 5.6 in.	18.7 lbs.
BLD-AM08N	70101101	849489063034	50849489063039	18.0 x 6.5 x 2.0 in.	2.8 lbs.	18.6 x 13.9 x 11.2 in.	3.0 lbs.
EMJ-0825	90600143	849489009322	50849489009327	6.9 x 3.9 x 2.2 in.	3.5 lbs.	16.5 x 8.1 x 6.2 in.	20.5 lbs.