

TC SERIES OUTDOOR LIGHTING

TC-WW-36W-RGBW-BT-BK
BLUETOOTH WG APP COMPATIBLE RGBW WALL WASH LIGHT


Customer Name: _____

Project Name: _____

Note: _____ | Type: _____



Selection:



3 3/4"(H) x 40"(W) x 3 1/2"(D)

The fixture has classic traditional appearance, professional light distribution design, 60-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Features

- Die-cast Aluminum Housing with Powder Coat Finish
- 7-Year Warranty
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors

Technical Specifications

Electrical:

- Voltage: 120-277V
- Power Factor: >0.9
- Wattage: 36W
- Efficacy: 36 LPW
- Operating Voltage: Max 900 mA, Max 36VDC
- Bluetooth Connection Range: Approximately 30 feet (10 meters). Maximum Communication Range Will Vary Depending On Obstacles (Person, Metal, Wall, etc.) Or Electromagnetic Environment.

Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish
- Solid State Lighting Technology for Long Life, No Maintenance Needed and High-Efficiency
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors
- 90° Adjustable Surface Mount Bracket
- High Conductive Aluminum LED Board
- Operating Temperature: -40°F to 104°F
- IP Rating: IP65, Suitable for Wet Locations
- 7-Year Warranty

Lighting:

- Dimming: Dimmable Through Phone App
- Total Lumens: 930LM (Single White)
1300LM (Maximum Power)
- Color Temperatures: RGBW Selectable Through Phone App
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 60°

Applications:



- The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Other Models:


- 72W | 2500LM | TC-WW-72W-RGBW-BT-BK



Photometrics: TC-WW-36W-RGBW-BT-BK



BUG Rating: B1-U1-G0



36W White, Area 20'x 20' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: TC-WW-36W-RGBW-BT-BK

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
TC-WW-36W-RGBW-BT-BK	36W	120-277V	930LM(Single White) 1300LM(Maximum Power)	RGBW	B1-U1-G0	36

Sample Ordering

Model	Wall Wash Light	Watt	Color Temp.	Bluetooth	Color
TC	WW	36W	RGBW	BT	BK

Accessories:

Blank = No Option For Accessories
 DMX-WW-SH2 = HALF GLARE SHIELD FOR TC-WW-36W/72W & DMX-WW-36W

ACCESSORIES:



DMX-WW-SH2
 Half Glare Shield for
 TC-WW-36W/72W &
 DMX-WW-36W

Example:

1. TC-WW-36W-RGBW-BT-BK (FOR TC 36W RGBW FIXTURE 120-277V)
2. TC-WW-36W-RGBW-BT-BK DMX-WW-SH2 (FOR TC 36W RGBW FIXTURE 120-277V)
 (HALF GLARE SHIELD FOR TC-WW-36W/72W & DMX-WW-36W)

