



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Traditional Wall Pack Series



Utilizing the latest generation of LED chips and a patented smart controller, this uniquely designed wall pack delivers a similar light output to a 150/200 W metal halide, but it also has multiple wattage and CCT to choose from. Housing made of die-casting aluminum with reliable powder coating. It is attractive in appearance and performance.

Specifications – 100W

CRI	<90	Ratings and Certifications	cULus, DLC Premium v5.1
Light Source	LED	Dimmable	No
Voltage	120-277	Beam Angle	Wide
Color Temperature	3000K / 4000K / 5000K	Mounting Options	Wall
Wattage	32W / 62W / 92W / 100W	Operating Temperature	-40°C to 40°C (-40°F to 104°F)
LPW	138	Lumens	14,075
Housing	Die-cast Aluminum	Finish	Bronze
Product Weight	6.75 lbs.	Product Dimensions	13.11" x 5.91" x 9.72"
Shipping Weight	7.75 lbs.	Shipping Dimensions	15" x 8" x 12"
Lifespan	>60,000	Warranty	5 Year





INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

Traditional Wall Pack			Example: WL-WP-46W-CWS-PC-BZ-G1		
Series	Wattage	CCT/Watt	Photocontrol	Color	Generation
WL-WP		CWS 3000K/4000K/5000K	PC Button photocell	BZ Bronze	G1
	46W	46W 16W/30W/42W/46W			
	100W	100W 32W/62W/92W/100W			

DLC Information

Item	DLC Version	DLC ID	Wattage	Lumens
WL-WP-46W-CWS-PC-BZ-G1	5.1 Premium	S-7IEPMV	16W/30W/42W/46W	6,520
WL-WP-100W-CWS-PC-BZ-G1	5.1 Premium	S-DOB8VI	32W/62W/92W/100W	14,075



INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Dimensions

Item	Length	Width	Height	Weight
WL-WP-46W-CWS-PC-BZ-G1	13.11"	5.91"	9.72"	6.5 lbs.
WL-WP-100W-CWS-PC-BZ-G1	13.11"	5.91"	9.72"	6.5 lbs.

