

UCLL 2x4

LED Low Profile Center Basket Recessed or Surface Mount

FEATURES & SPECIFICATIONS

INTENDED USE

Low profile LED center lens fixtures are ideal for shallow plenum spaces. Specification grade, direct / indirect center diffuser appearance luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces provide a softened “sky light” appearance to the modern office environment. Linear ribbed lens encloses the LED array and is designed to maximize efficiency and minimize glare.



SIZE W x L x H in inches


24”W x 48”L x 3.25”D

MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Luminaire body finish is high reflectance baked white enamel, with matte white re-reflectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is ribbed acrylic lens provides increased light output.



Specially designed lens (LL) for LED Array to provide enhanced light transmission while minimizing glare and LED diode shadows.



Shroud for surface mounted.

- Matte white reflective surfaces for soft, uniform light distribution

ORDERING INFORMATION

Example: UCLL24LF32W3450LDMV40K

STANDARD

UC	LL	24L	F32W3450L	DMV	40K
Series	Lens Material	Size	Wattage and Lumen	Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens PF Perforated Basket	24L	F32W3450L 32 System Watts, 3450 Delivered Lumens F48W4800L 48 System Watts, 4800 Delivered Lumens F57W5400L 57 System Watts, 5400 Delivered Lumens	DMV 0-10V Dimming	30K 3000K 35K 3500K 40K 4000K 50K 5000K
SHUC Center Basket Surface Mount					
SSUC Center Basket Sensor - On/Off					
			Value Line		
			V45Y 5000N 45 System Watts, 5000 Delivered Lumens		

HIGH OUTPUT

UC	LL	24L	H72W7000L	DMV	40K
Series	Lens Material	Size	Wattage and Lumen	Driver	Color Temperature
UC Center Basket Grid Mount	LL Linear Ribbed Lens PF Perforated Basket	24L	H72W7000L 72 System Watts, 7000 Delivered Lumens	DMV 0-10V Dimming	30K 3000K 35K 3500K 40K 4000K 50K 5000K
SHUC Center Basket Surface Mount					
SSUC Center Basket Sensor - On/Off					

*Consult FACTORY for more options

Catalog Number:
Notes: