



T E X A S

F L U O R E S C E N T S

UCLL 1x4

NGF 'Nqy 'Rt qPig'Egpgvt 'Dcungv
Tgegugf 'qt 'Uwt lrcg'O qwpv

FEATURES & SPECIFICATIONS

INTENDED USE

Low profile LED center lens fixtures are ideal for shallow plenum spaces. Specification grade, direct / indirect center diffuser appearance luminaire provides smooth and uniform ambient lighting for all commercial and industrial buildings with recessed configurations. Reflected light from matte surfaces provide a softened "sky light" appearance to the modern office environment. Linear ribbed lens encloses the LED array and is designed to maximize efficiency and minimize glare.

SIZE W x L x H in inches

11.7"W x 47.8"L x 3.25"D


MATERIALS & FEATURES

Housing is die-formed and embossed code 22 gage steel. Luminaire body finish is high reflectance baked white enamel, with matte white re-reflectors. Wiring knockouts are provided on the back of housing. Center diffuser snaps into place; no tools are required for removal. Diffuser is ribbed acrylic lens provides increased light output.

- Direct / indirect mimics "sky light" appearance
- Matte white reflective surfaces for soft, uniform light distribution



Specially designed lens (LL) for LED Array to provide enhanced light transmission while minimizing glare and LED diode shadows.



Shroud for surface mounted.

MOUNTING

Recessed inverted T-Bar ceilings. Grid mount or Surface Mount.

ORDERING INFORMATION

EF3@63D6

Example: UCLL14LHPSW%&"LDMV40K

WE	NN	36N	HPSY %&"N	FOX	62M
Ugt lgu	Ngpu'O cvgt lcn	Ukt g	Y cwei g'TNwo gp	Driver	Eqmt 'Vgo rgt awt g'
WE" Center Basket Grid Mount	NN Linear Ribbed Lens BB Perforated Basket	36N	H54Y 56" N 32 System Watts, 3463 Delivered Lumens H6: Y 6: ""N 48 System Watts, 4813 Delivered Lumens H79Y 76""N 57 System Watts, 5400 Delivered Lumens	DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire	52M' 3000K 57M' 3500K &'= 4000K ' '= 5000K

: ;9: AGFBGF

WE	NN	36N	J 94Y 9222N	FOX	62M
Ugt lgu	Ngpu'O cvgt lcn	Ukt g	Y cwei g'TNwo gp"	Driver	Eqmt 'Vgo rgt awt g'
WE" Center Basket Grid Mount	NN Linear Ribbed Lens BB Perforated Basket	36N	J 94Y) ""N 94 System Watts, 7000 Delivered Lumens	DMV 0-10V Dimming *Field installed-Dimming Wire DMVFID 0-10V Dimming *Factory installed-Dimming Wire	52M' 3000K 57M' 3500K &'= 4000K ' '= 5000K

f15a` egf'835FADKXd_ adWbf'a` e

Texas Fluorescents

2055 Luna Rd. Suite 142 Carrollton, TX 75006

Phone: 972-247-3171 Fax: 972-247-0200

www.texasfluorescents.com email: sales@texasfluorescents.com

Catalog Number:
Notes: