

VTJ VAPOR TIGHT JELLY JAR

DESCRIPTION

naturaLED® VaporTight Jelly Jar (VTJ) are designed to replace incandescent and CFL fixtures with long-lasting illumination over doorways, scaffolding, construction sites, and many more applications. Our naturaLED® LED VaporTight Jelly Jars are IP65 Rated against ingress of dust, pressurized water and harsh environments. Constructed with cast aluminum housing and glass lens. Available in two different mounting options: ceiling and wall, 65% less energy and zero maintenance cost for up to 50,000+ average life hours.

APPLICATIONS

Warehouse , Security, Pathway, Doorway, Scaffolding, Fire Hydrants, Construction Sites Lighting

FEATURES

- Energy Star Qualified
- ETL Listed
- IP65 Rated
- Frosted glass diffuser provides you glare-free light
- High efficacy with 90 lumen per watt
- High- temperature silicone gasket protects against moisture and dust
- Color Temp: 3000K, 4000K
- Input line voltage: 120-277V
- CRI: 80
- Surge Protection: 2KV
- Available in wall or ceiling mount
- Material: die cast aluminum / glass
- Four 1/2" conduit entries for easy wiring
- Operating temperature: - 4°F - 122°F
- 5 Year Warranty
- Finish: Silver

PROJECT:

SCHEDULE:

DATE:

PREPARE BY:

NOTES:




Rated Life 50,000 Hours
Warranty 5 Years

ACCESSORIES



REPLACEMENT SAVINGS



Replace Incandescent and CFL with LED

SAMPLE NUMBER LED-FXVTJ20/830/MV-WM

STYLE	FAMILY	SERIES	WATTAGE	CRI/COLOR TEMP	MV	WM
LED	FX	VTJ	20	830	MV	WM
LED Lighting	Fixture	Vapor Tight Jelly Jar	20 Watt	CRI 80 3000K	Multiple Voltage	Wall Mounting (CM) Ceiling Mounting



VAPOR TIGHT JELLY JAR


WALL & AREA LUMINAIRES

ORDERING


Watts (W)	Ordering Code	Description	CCT (K)	Lumens (Lm)	Equiv. Wattage (W)	Mount	IP65 Rated	Energy Star
20	7604	LED-FXVTJ20/830/MV-WM	3000K	1,713	150	Wall	•	•
20	7605	LED-FXVTJ20/840/MV-WM	4000K	1,713	150	Wall	•	•
20	7606	LED-FXVTJ20/830/MV-CM	3000K	1,713	150	Ceiling	•	•
20	7607	LED-FXVTJ20/840/MV-CM	4000K	1,713	150	Ceiling	•	•

DIMENSIONS

20W - Wall Mount 3.80-lbs



20W - Ceiling Mount 3.80-lbs



ACCESSORIES (Ordered Separately)


Replacement Lens



P10169 LENS-VTJ
(Replacement Lens for Vapor Tight Jelly Jar)

PHOTOMETRICS CHART

20 Watt Energy Star



Center Beam fc	Beam Width
2.5R	59.6 fc 20.4 ft 20.3 ft
5.0R	14.9 fc 40.0 ft 40.7 ft
7.5R	6.62 fc 61.2 ft 61.0 ft
10.0R	3.73 fc 81.6 ft 81.4 ft
12.5R	2.38 fc 102.0 ft 101.7 ft
15.0R	1.66 fc 122.4 ft 122.0 ft

■ Vert. Spread: 152.8°
■ Horiz. Spread: 152.4°

PACKAGE

Case Qty 1 pc

