# WHL-CLPU

## **ALL LED EXIT &** STOM SIGNAGE AVAILABL **EMERGENCY LIGHTPIPE** THERMOPLASTIC COMBO

STANDARD



Your custom wording here!











Patent No: US, 8,024,880 B2

#### **ILLUMINATION**

- Ultra bright, energy efficient white LED emergency lighting.
- 4.5 watt (36 LEDs x 0.125 watts) per light pipe.
- Adjustable high performance, smooth, chrome-plated, metallized reflector and acrylic, UV-stabilized "Light Pipe" lens for optimal light distribution.
- Long life, energy efficient Red or Green LED EXIT sign illumination.

#### **ELECTRICAL**

- Dual 120/277 voltage.
- Charge rate/power "ON" LED indicator light and push-to-test switch for mandated code compliance testing.
- 4.8V long life, maintenance-free, rechargeable NiCd battery.
- Remote capacity of 3.0 watts standard.
- Internal solid-state transfer switch automatically connects the internal battery to LED board and LED Light Pipe for minimum 90-minute emergency illumination.
- Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

### **MOUNTING**

- EZ-snap mounting canopy included for top or end mount.
- Universal knockout pattern on back plate for wall mount.

#### HOUSING

- Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant, thermoplastic in white or black finishes.
- EZ snap-out Chevron directional indicators.


#### **OPTIONS**

- SDT: Self-diagnostic feature performs monthly, biannual, and annual tests to ensure reliable operation and meets electrical and life safety codes.
- Custom: Signs available with requested "special" wording.

#### **WARRANTY / LISTING**

- Five year warranty on all electronics and housing. Battery prorated for five years.
- Meets UL924, NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes.
- UL Listed for damp locations (0°C 50°C).
- Certified to CEC under Title 20 Regulations.

#### **DIMENSIONS**



#### Sample Part Number: WHL-CLPU2RWRC

**ORDERING INFORMATION** MODEL No. of FACES LETTER COLOR HOUSING COLOR OPTIONS Special voltage & SALIDA WHL-CLPU Universal Red White RC Remote Capable SDT Self-Diagnostics face plate options available. Single/Double (Standard) G Green В Black **CUSTOM** Custom Wording Check with your Best Face Lighting Representative.

