



INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

# Bullet Flood Light Series



This compact but powerful flood light is a true innovation practically and aesthetically. The upgraded tuning switch allows for easy access to a range of CCTs and wattages based on different environments. Utilizing performance optics and long-lasting driver, these landscape flood lights will last for years to come.

## Specifications

CRI	83	Ratings and Certifications	UL, RoHS, DLC Premium 5.1
Light Source	LED	Dimmable	0-10v
Voltage	120-277v	Beam Angle	25° or 45°
Color Temperature	3000K/4000K/5000K	Mounting Options	Ground
Wattage	9W/16W/24W	Operating Temperature	-40°C to 40°C (-40°F to 104°F)
LPW	133	Lumens	1,200 – 3,200
Housing	Die-cast Aluminum	Finish	Bronze
Product Weight	3 lbs.	Product Dimensions	L 7.24" x W 5.99" x H 8.17"
Shipping Weight	3.5 lbs.	Shipping Dimensions	L 8" x W 6" x H 9"
Lifespan	50,000	Warranty	5 Years





INDUSTRIAL AND COMMERCIAL  
LIGHTING MFR SINCE 2003

PROJECT NAME \_\_\_\_\_  
ITEM # \_\_\_\_\_  
FIXTURE SCHEDULE \_\_\_\_\_  
NOTES \_\_\_\_\_

## Order Information

Bullet Flood				Example: WL-FLBL-C24WS-25D-BZ-PC-G1	
Series	Wattage/CCT	Degree	Finish	Photocell	Generation
WL-FLBL	Watt Select 9W 16W 24W  CCT Select 3000K 4000K 5000K	25D  or  45D	BZ	PC	G1

## Dimensions

Item	Length	Width	Height	Weight
WL-FLBL-C24WS-25D-BZ-PC-G1	7.24"	5.99"	8.17"	3 lbs.
WL-FLBL-C24WS-45D-BZ-PC-G1	7.24"	5.99"	8.17"	3 lbs.

