



WAREHOUSE-LIGHTING.COM
INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Wallmount/Mini-Wallpack G2 Series



This LED wall mount is powerful, waterproof, and compatible with universal voltage. It has a diecast aluminum housing and anti-corrosion priming. This fixture has an integrated photocell.

Specifications

CRI	>80	Ratings and Certifications	cULus, DLC Premium v5.1
Light Source	LED	BUG	B1-U3-G2
Dimmable	0-10V	Voltage	120-277V
CCT	5000K	Mounting Options	Wall Mount
Wattage	20W	Operating Temperature	-40° C to 45° C (-40° F to 113° F)
LPW	142	Lumens	2840
Product Weight	2.29 lbs.	Product Dimensions	5.79" L x 3.07" W x 8.58" H
Shipping Weight	2.65 lbs.	Shipping Dimensions	6.06" L x 3.46" W x 8.86" H
Housing	Die Cast Aluminum	Finish	Bronze
Surge	2.5 kV	Warranty	5 year limited

*Data is considered to be representative of the series. Actual production may vary between up to ±10% of initial delivered lumens.





WAREHOUSE-LIGHTING.COM

INDUSTRIAL AND COMMERCIAL
LIGHTING MFR SINCE 2003

PROJECT NAME _____
ITEM # _____
FIXTURE SCHEDULE _____
NOTES _____

Order Information

Wallmount Series			Example: WL-MWP-20W-50K-B-MV-PC-G2			
Series	Wattage	CCT	Finish	Voltage	Photocell	Generation
WL-MWP	20W 20 Watts	50K 5000K	B Bronze	MV Universal Voltage 120-277V	PC Photocell	G2

Dimensions

Item	Length	Width	Height	Weight
WL-MWP-20W-50K-B-MV-PC-G2	5.79"	3.07"	8.58"	2.29 lbs.

