

PROJECT NAME
ITEM #
FIXTURE SCHEDULE
NOTES

Full Cutoff Wall Pack Series



Our Full Cutoff LED Wall Pack Light offers the perfect solution when you need to brightly illuminate the perimeter of a building while controlling the sideways spread of light. Thanks to its down throw beam angle and type IV distribution pattern, this premium LED wall pack fixture casts a uniform, focused ray in a circular pattern downward and outward along a wall and to the ground directly beneath. Areas away from the building, meanwhile, remain dark. This creates a visually appealing illumination while enhancing safety and security where it's needed.

Specifications – 120W

CRI	>80	Ratings and Certifications	DLC Premium v5.1, UL Listed, IP65
Light Source	LED	Dimmable	0-10v
Voltage	120-277∨	Beam Angle	Down Throw
Color Temperature Selectable	3000K / 4000K / 5000K	Mounting Options	Wall
Wattage	120W	Operating Temperature	-40°C to 50°C (-40°F to 122°F)
LPW	129-143	Lumens	15,610-16,450
Housing	Die-cast Aluminum	Finish	Bronze
Product Weight	7.05 lbs.	Product Dimensions	12.8" L x 6.38" W x 9.53" H
Shipping Weight	9.04 lbs lbs.	Shipping Dimensions	14.06" L x 8.74" W x 12.01" H
Lifespan	50,000	Warranty	5 Year









PROJECT NAME
ITEM #
FIXTURE SCHEDULE
NOTES

Order Information

Full Cutoff Wall Pack		Example: WLFC-40W-3CTS-10D-PC-BZ-G1				
Series	Wattage	Select CCT	Dimming	Photocell	Finish	Generation
WLFC	40W 80W 120W	3CTS 3000K/4000K/5000K	10D 0-10V	PC	BZ	Gl

DLC Information

Item	DLC Version	DLC ID	Wattage	Lumens
WLFC-40W-3CTS-10D-PC-BZ-G1	5.1 Premium	S-CVW3AG	41.3W	5,556
WLFC-80W-3CTS-10D-PC-BZ-G1	5.1 Premium	S-20EC8B	80.1W	10,801
WLFC-120W-3CTS-10D-PC-BZ-G1	5.1 Premium	S-KTZ1OG	120.5W	15,611


Dimensions


Item	Length	Width	Height	Weight
WLFC-40W-3CTS-10D-PC-BZ-G1	9.81"	6"	8.03"	4.85 lbs.
WLFC-80W-3CTS-10D-PC-BZ-G1	12.8"	6.38"	9.53"	7.05 lbs.
WLFC-120W-3CTS-10D-PC-BZ-G1	12.8"	6.38"	9.53"	7.05 lbs.



PROJECT NAME
ITEM #
FIXTURE SCHEDULE
NOTES

WLFC 40W





WLFC 80W & 120W

