




# HI-LITE MFG. CO., INC.

13450 Monte Vista Avenue  
Chino, California 91710  
Telephone: (909) 465-1999  
Fax: (909) 465-0907

Job Name: \_\_\_\_\_  
Type: \_\_\_\_\_  
Quantity: \_\_\_\_\_

## Angle Shade Collection



Item Number	Height (A)	Width (B)
H-18107	8"	7"
H-18110	10-1/2"	10"
H-18112	12"	12"
H-18114	14-1/2"	14"

Fixture No.	Fixture Color	Mounting	Mounting Color	Optional Accessories	Accessory Color	Wattage/Lamp options	Ballast	Voltage
<b>H-18107</b> <sup>(1)</sup>	Standard <sup>(2)</sup>	Mounting Options	Standard	<b>CGU</b>	Standard	Incandescent (6)	Ballast option not available for INC.	Incandescent
<b>H-18110</b> <sup>(1)</sup>	91 (Black)	1/2"	91 (Black)	(Cast guard & glass)	91 (Black)	(Fixture is standard 200W. Do not specify)	RB <sup>(4)</sup>	(Fixture is standard 120V. Do not specify.)
<b>H-18112</b>	93 (White)	3/4"	93 (White)	<b>LCGU</b>	93 (White)	CFL (3) (6)	(Remote)	CFL
<b>H-18114</b>	95 (Dk. Grn)	Stem Options (Stem 1/2")	95 (Dk. Grn)	(Large cast guard & glass)	95 (Dk. Grn)	(Compact Fluorescent)	<b>BCM</b>	(Multi 120/277V)
	96 (Galv.)	___ST	96 (Galv.)	<b>WGU</b>	96 (Galv.)	13/CFL	(Canopy Mount)	HID
	<b>BR47</b> (Rust)	Specify length and canopy.	<b>BR47</b> (Rust)	(Wire guard & glass)	<b>BR47</b> (Rust)	18/CFL	<b>PLB</b> <sup>(5)</sup>	RB and BCM
	<b>BK01, GN20.</b>	<b>HSC</b> (Canopy)	For all finishes see pages 344-348.	<b>LWGU</b>	For all finishes see pages 344-348.	26/CFL	(Postline)	<b>M</b>
	Upgraded Finishes.	<b>SMC</b> (Canopy)		(Large wire guard & glass)		26/32/42/CFL	For specs see pages 341-343.	(Multi 120/208/240/277V)
	29, 66, 82, 90, 92, 94, 97, 99, 100, 103, 104, 105, 110, 112, 113, 114, 115, 117, 118, 119, 120, 127, 128, 129, 133, 134, 135, 136, 98,	Flush Mount Options		<b>WGR</b>		32/CFL		PLB
	101, 102, 137, 138, 139, 140, 121, 122, 123, 124, 125, 126, 11, 01, 22, 25, 33, 77, 89, 24, 44, 48, 49, 15, 16.	<b>FHSC</b>		(Wire guard)		42/CFL		1 (120V)
	For finish specs see pages 344-348.	<b>FSMC</b>		<b>SK</b>		57/CFL		2 (277V)
		Arm Options		(Swivel knuckle)		<b>DMB</b>		
		<b>B-1 HL-K</b>		For specs and glass color see pages 321-344.		(Dimmable Ballast for CFL. Add to Part No.)		
		<b>HL-A HL-U</b>				HID <sup>(3)</sup>		
		<b>HL-H P-1</b>				(High Intensity Discharge)		
		<b>HL-C P-3</b>				MH <sup>(3) (6)</sup>		
		<b>HL-D</b>				(Metal Halide)		
		For all arms and specs see pages 321-344.				35/MH		
						50/MH		
						70/MH		
						100/MH		
						150/MH		
						175/MH		
						HPS <sup>(3) (6)</sup>		
						(High Pressure Sodium)		
						50/HPS		
						70/HPS		
						100/HPS		
						150/HPS		
						LED		
						20W	LED	LED
						30W	See specifications for complete part number.	See specifications for complete part number.

H-18110	-	91	/	1/2"	-	91	/	CGU-CLR	-	91	/	13/CFL	-	BCM	-	M
---------	---	----	---	------	---	----	---	---------	---	----	---	--------	---	-----	---	---

### ORDER EXAMPLE

(USE THIS FORMAT TO PLACE ORDER)

#### Notes:

- (1) H-18107 not available with glass enclosures. H-18107 available for 200W Max INC, 32W Max CFL and 100W Max HID. H-18110 not available with LWGU, LCGU, ARN or LARN.
- (2) For interior finish of fixture refer to color chart on pages 344-348.
- (3) Requires Globe Option. (See pages 339-341 for Globe Options)  
Max Wattages for CGU and WGU are 100W INC, 32W CFL and 100W HID.  
Max Wattages for LWGU, LCGU, ARN and LARN are 200W INC, 57W CFL and 175W HID.
- (4) (RB) Remote Ballast not available for Fluorescent Lamping.
- (5) (PLB) Post Line Ballast must specify 120V or 277V.  
(PLB) 50W MH requires a 3" dia. pole.  
(PLB) 70W and 100W MH require a 4" dia. pole.  
(PLB) 50W, 70W, 100W and 150W HPS require a 3" dia. pole.
- (6) Socket Bases: INC and HID are medium base, CFL are GX24Q.

Suitable for wet location.