# LED CANOPY LUMINAIRE

Project Information				
Туре				
Name				

Voltage

### **Product Description**

LED Canopy Light luminaire has a beautiful low profile design intended for gas stations or other commercial lighting applications, Supports ceiling mount or conduit pipe mount. High-performance illumination that lasts 50,000 hrs. It's ideal for replacing 250-400W Metal Halide fixtures..





**Application:** 

Widely used in Gas Station, service Stations etc.



### **Electric Characteristic**

Specification/Model	LS-NCPV4-150WSAS-ab			
Housing	Die-casting Aluminum Alloy			
Input power	150W			
Lumens output	19500LM			
Efficiency	130LM/W			
Mounting	Pendant / Surface Mount			
Color Temperature	4000K/4500K/5000K/5700K			
Input voltage	100-277V UL Driver			
Dimension	15 *15 in			
Waterproof Rating	IP 65			
Working temperature	-40-+45°C			
Junction temperature	<75℃			
lamps efficiency	≥90%			
Certificates	DLC UL			
Equivalent	250-400W MH/HPS			





#### **Ordering Information**


Example: LS-NCPV4-150WSAS-40K-T

Product	Power	Replacement	Color Temperature	Furnish
LS-NCPV4-150WSAS-ab	150W	250-300W MH/HPS	40K 4000K 45K 4500K 50K 5000K 57K 5700K	T-White


## **Installation Options**








#### **Photometrics**





# **Projected LED Lumen Maintenance**

Operating hours	0	25000	50000
Lumen maintenace factor	1	0.91	0.8

Data references the extrapolated performance projections for the Canopy LED platform in a 25°C ambient, based on 10,000 hours of LED testing (tested per IESNA LM - 80-08 and projected per IESNA TM-21-11).

# **Dimensions**

