




HI-LITE MFG. CO., INC.

13450 Monte Vista Avenue
Chino, California 91710
Telephone: (909) 465-1999
Toll Free: (800) 465-0211
Fax: (909) 465-0907
www.hilitemfg.com

Job Name: _____
Type: _____
Quantity: _____

Galileo Collection



Item Number	Height (A)	Width (B)
H-30132	14"	12"
H-30136	19"	16"

Fixture No.	Fixture Color	Mounting	Mounting Color	Optional Accessories	Accessory Color	Wattage/Lamp options	Ballast	Voltage
H-30132 H-30136	Standard (1) 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust) BK01, GN20 . Upgraded (1) Finishes 29, 66, 82, 92, 97, 100, 103, 104, 105, 112, 113, 114, 117, 118, 119, 127, 128, 133, 134, 135, 136, 98, 101, 102, 137, 139, 140, 121, 122, 123, 124, 11. For finish specs see pages 344-348.	Cord Options (2) CB8 (8' Blk Cord) CW8 (8' Wht Cord) CG8 (8' Gray Mesh Cord) Custom Cord Options (2) CB (Black) CW (White) CG (Gray Mesh) Specify length. Stem Options (Stem 1/2") ST Specify length and canopy. HSC (Canopy) SMC (Canopy) Flush Mount Options FHSC FSMC For all arms and specs see pages 321-344.	Standard 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust) For all finishes see pages 344-348.	CLLS (3) (Conical Lens) SDL (3) (Smooth Domed Lens) SFL (3) (Smooth Flat Lens) DPL (3) (Drop Lens) FX (Flexible tubing for cord mounted fixtures only) For specs see pages 321-344.	RIB (Clear Ribbed) CLR (Clear) FR (Frost) CLR (Clear) FR (Frost) RIB (Clear Ribbed) Standard 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust) For all finishes see pages 344-348.	Incandescent (5) (Fixture is standard 200W. Do not specify.) CFL (5) (Compact Fluorescent) 13/CFL 18/CFL 26/32/42/CFL 26/CFL 32/CFL 42/CFL 57/CFL DMB (Dimmable Ballast for CFL. Add to Part No.) HID (High Intensity Discharge) MH (5) (Metal Halide) 35/MH 50/MH 70/MH 100/MH 150/MH 175/MH HPS (5) (High Pressure Sodium) 50/HPS 70/HPS 100/HPS 150/HPS LED See LED specification sheet.	Ballast option not available for INC. RB (4) (Remote) BCM (Canopy Mount) OBB (Onboard Ballast) OBB (Fluorescent Options 13W-57W) OBB (HID Options 35W-100W) For specs see pages 341-343. LED See specifications for complete part number.	Incandescent (Fixture is standard 120V. Do not specify.) CFL M (Multi 120/277V) HID RB and BCM M (Multi 120/208/ 240/277V) LED See specifications for complete part number.

H-30132 - 91 / 1/2" - 91 / CLLS - 91 / 13/CFL - BCM - M

ORDER EXAMPLE

(USE THIS FORMAT TO PLACE ORDER)

Notes:

- (1) For interior finish of fixture refer to color chart on pages 344-348.
- (2) Cord Mounting wattage not to exceed 100 for HID. Gray Mesh Cord not available for HID.
- (3) CLLS available for both fixtures. SDL available for H-30132 only. SFL available for both fixtures. DPL available for H-30136 only.
- (4) (RB) Remote Ballast not available for Fluorescent Lamping.
- (5) Socket Bases: INC and HID are medium base. CFL is GX24Q.

Suitable for dry location only.