

HI-LITE MFG. CO., INC.

13450 Monte Vista Avenue Chino, California 91710 Telephone: (909) 465-1999 Toll Free: (800) 465-0211 Fax: (909) 465-0907 www.hilitemfg.com

	Job Name.
	Type:
	Quantity:
ı	

Radial Vapor Jar Collection

Α

Item	Height	Width	Length	Projection
Number	(A)	(B)	(C)	(D)
H-CGU-RS-8-2B	10"	8"	20"	10"
H-CGU-RS-9-2B	10"	9 1/2"	22"	11"
H-LCGU-RS-10-2B	13"	10"	22 1/2"	12"
H-LCGU-RS-12-2B	13"	12"	30"	15"

For Wall Mount Only

H-LCGU-RS-12-2B	3" 12"	30" 15"						<u> </u>
Fixture No.	Fixture Color	Glass Color	/ Wattage/ Lamp options -	Ballast –	Voltage	HILITE MES	 В	10 Miles
H-CGU-RS-8-2B ⁽¹⁾ H-CGU-RS-9-2B ⁽¹⁾ H-LCGU-RS-10-2B ⁽¹⁾ H-LCGU-RS-12-2B ⁽¹⁾	Standard 91 (Black) 93 (White) 95 (Dk. Grn) 96 (Galv.) BR47 (Rust) BK01, GN20. Upgraded Finishes.(2) 29, 66, 82, 90, 92, 94, 97, 99, 100, 103, 104, 105, 110, 112, 113, 114, 115, 117, 118, 119, 120, 127, 128, 129, 133, 134, 135, 136, 98, 101, 102, 137, 138, 139, 140, 121, 122, 123, 124, 125, 126, 11, 01, 22, 25, 33, 77. 89, 24, 44, 48, 49. For finish specs see pages 344-348.	CLR (Clear) RIB (Clear Ribbed) FR (Frost) RD (Red) BL (Blue) GRN (Green) AM (Amber) Crackle)	Incandescent (1) (4) (Fixture is standard 2-100W or 2-200W. Do not specify.) CFL (4) (Compact Fluorescent) 2-13/CFL 2-18/CFL 2-26/32/42/CFL 2-26/CFL 2-32/CFL 2-42/CFL 2-42/CFL 2-57/CFL DMB (Dimmable Ballast for CFL. Add to Part No.) HID (High Intensity Discharge) MH (4) (Metal Halide) 2-35/MH 2-50/MH 2-100/MH 2-1100/MH 2-175/MH HPS (4) (High Pressure Sodium) 2-50/HPS 2-100/HPS 2-100/HPS 2-150/HPS LED 20W 30W	Ballast option not available for INC For CFL only BCM (3) (Canopy Mount) For HID only RB(2) (Remote) For specs see pages 341-343.	Incandescent (Fixture is standard 120V. Do not specify.) CFL M (Multi 120/277V) HID RB and BCM M (Multi 120/208/240/277V)	HILLE MO Control of the Control of t	4 3/4" 3 1/2" Mounting Detail	HILL OF THE PARTY
H-CGU-RS-8-2B -	. 91	- CLR	/ 2-13/CFL	- BCM -	- M			

ORDER EXAMPLE

(USE THIS FORMAT TO PLACE ORDER)

Notes

- H-CGU-RS-8-2B and H-CGU-RS-9-2B available for 2-100W Max INC, 2-32W Max CFL and 2-100W Max HID. H-LCGU-RS-10-2B and H-LCGU-RS-12-2B available for 2-200W Max INC, 2-57W Max CFL and 2-175W Max HID. Above fixtures available with WGU wireguard.
- (2) Casting will painted to match copper and brass finishes.
- (3) (RB) Remote Ballast not available for Fluorescent Lamping. (BCM) Ballast Canopy Mount not available for HID Lamping.
- (4) Socket Bases: INC and HID are medium base, CFL are GX24Q.

Suitable for wet location.