

S11902

3W/LED/T5/840/BP 3 watt T5 LED; Miniature bi-pin base; 4000K; 50000 Average rated hours; 270 lumens; 120-277 volts

Features

- No ballast or external driver required
 Available in 6", 9", 12", & 21"
- Available in 6, 9, 12, & 21
 Direct wire 120-277V line voltage
 Double ended wiring
 NSF Approved
 PET Shatterproof coated
 5 year Limited warranty

S11902

Replaces F6T5/CW lamps

Item Number	UPC		Voltage	Watts	Operating Frequency		Fluorescent Equivalent			Power Factor	Lamp Shape
S11902	045923119026		120-277	3	50	/60Hz	6W		0.90		T5
Base	ANSI Base	Lamp Code			Dimmable/Non- Dimmable		Finish	MOL Ir		IOD In nches	Initial Lumens
Miniature Bi- Pin	G5	3W/LED	/T5/840/BF	P 1	Non-Dimmable		Frosted	8-29/32	2" (0-5/8''	270
Average Rated Hours	Kelvin Temp	Cole	or CRI	Beam S _l Deg		Operatin	ng Tempera	iture	Pack	CE	C Status
50000	4000	Coc Whi	80	240)	, ,	C (-13F) to a maximum of +45C (+113F)		10	Lawful for sale in California	
Material	RoHS Compliant		UL or E	UL or ETL Listed		UL Classification				Warranty	
Glass	Ye	es	•	Yes		cULus Classified - Damp Location Rated				5 Year Limited	



National Toll-Free: 800.43.SATCO (800.437.2826) www.satco.com Distribution Centers: New York, Florida, Texas, Washington, California, Puerto Rico Corporate Offices: 110 Heartland Blvd., Brentwood, NY 11717 800.437.2826 631.243.2022 Fax 631.243.2027



©2012, Satco Products, Inc. Not responsible for typographical errors. 06/12 S1051