



Recommendations	
Product Overview	
Product Code	EA0055
Industry	Inks
Application	Screen Printing
Category	Specialty Inks
Sub-Category	Puff
Chemistry	Plastisol
Substrate(s)	Other
Best Used By	12 months
Certification(s)	ISO9001
Performance:	
After Flash Tack	Decreases with increased mesh
Squeegee:	
Squeegee Profile	Square
Squeegee Type	Polyurethane
Screen:	
Emulsion Type	Capillary film, Direct, Indirect

Last Change: Feb 2017

NPT PUFF ADDITIVE

EA0055 is a puff concentrate. Use at up to 15% by weight to make a puff ink from any NPT opaque plastisol color. Mix thoroughly. EA0055 may also be used to take the gloss from plastisol ink. Add 2% by weight to an NPT plastisol ink to make a matte finish.

Features

- Creamy plastisol for easy printing.
- Low tack formulation for fast shearing action.
- Creamy plastisol for easy printing.
- Low tack formulation for fast shearing action.

Statement

Rutland Plastic Technologies does not knowingly add plasticizers containing the phthalates listed and outlined in California Bill 1108, CPSIA HR-4040 and Oeko-tex Standard 100. The plasticizers identified may include di-(2-ethylhexyl) phthalate (DEHP), dibutyl phthalate (DBP), benzyl butyl phthalate (BBP), diisononyl phthalate (DINP), diisodecyl phthalate (DIDP), di-n-octyl phthalate (DnOP), (DIBP) Di-iso-butyl, and (DMP) Dimethylphthalate, including esters of ortho-phthalic acid and are not direct ingredients in the manufacture of Clairra High Opacity Non-Phthalate Inks. Rutland Plastic Technologies does not test the final product for amounts of the aforementioned phthalate plasticizers and esters and encourages all users to conduct testing for their intended use.

Disclaimer:

Not all Rutland products are available in every country. Please check with your local representative for availability. The data presented in this leaflet are in accordance with the present state of our knowledge, but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the products for a particular purpose.