

1.	Product Identification			
	Trade name :	PHOTOCURE WSR		
	SDS Number ;	A-340C-E2U		
	Manufacturer's name :	Murakami Screen U.S.A., Inc,		
	Addres ;	745 Monterey Pass Road, Monterey Park, California, U.S.A.		
	Phone number ;	(323) 980-0662		
	FAX number ;	(323) 980-0659		
	Emergency phone number ;	Infotrac (800) 535-5053		
	Recommended use of chemical and res	trictions on use:		
		Material for screen printing. Not inten	ded for other applications	
2.	Hazard identification			
	GHS classification :			
	Physical hazards ;			
	Explosives		Not applicable	
	Flammable gases		Not applicable	
	Flammable aerosols		Not applicable	
	Oxidizing gases		Not applicable	
	Gases under pressure		Not applicable	
	Flammable liquids		Not classified	
	Flammable solids		Not applicable	
	Self-reactive substances and mixture	S	Classification not possible	
	Pyrophoric liquids		Not classified	
	Pyrophoric solids		Not applicable	
	Self-heating substances and mixtures	:	Classification not possible	
		ontact with water, emit flammable gase		
	Oxidizing liquids		Not applicable	
	Oxidizing solids		Not applicable	
	Organic peroxides		Not applicable	
	Corrosive metals		Classification not possible	
	Health hazards ;			
	Acute toxicity (Oral)		Classification not possible	
	Acute toxicity (Dermal)		Classification not possible	
	Acute toxicity (Inhalation : Gases)	х.	Classification not possible	
	Acute toxicity (Inhalation : Vapours		Classification not possible	
	Acute toxicity (Inhalation : Dusts an	d Mists)	Classification not possible	
	Skin corrosion/irritation		Category 2	
	Eye damage/eye irritation		Category 2	
	Respiratory sensitization		Classification not possible	
	Skin sensitization		Category 1	
	Germ cell mutagenicity		Classification not possible	
	Carcinogenicity Bonno ductivo tovioity		Classification not possible Classification not possible	
	Reproductive toxicity		Classification not possible	
	Specfic target organ toxicity (Single	e exposure/	Classification not possible	



Trade name : PHOTOCURE WSR SDS Number : A-340C-E2U Edited : JANUARY 3, 2017 Revised : FEBRUARY 21, 2017 Printed : FEBRUARY 21, 2017

Specfic target or	gan toxicity (Repeated exposure)			
	Classification not possible			
Aspiration hazar	rd	Classification not possible		
Environmental ha	izards ;			
Hazardous to the	e aquatic environment (Acute toxicity)	Category 3		
Hazardous to the aquatic environment (Chronic toxicity)		Classification not possible		
Hazardous to the ozone layer		Classification not possible		
Pictogram and Syn	nbol :			
	Exclamation mark			
Signal Word :	Warning			
	H315 Causes skin irritation			
	H317 May cause an allergic skin reaction			
	H319 Causes serious eye irritation			
-	H402 Harmful to aquatic life			
Precautionary state	ements : P261 Avoid breathing dust/fume/gas/mist/vapo			
	P264 Wash hands thoroughly after handling.	urs/spray.		
	P272 Contaminated work clothing should not b	a allowed out of the workplace		
	P273 Avoid release to the environment.	anowed out of the workplace.		
		g/eve protection/face protection		
Response ;	P280 Wear protective gloves/protective clothing/eye protection/face protection. P302+P352 IF ON SKIN: Wash with plenty of water.			
Response,	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.			
		ict lenses, if present and easy to do. Continue rinsing.		
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.			
	P337+P313 If eye irritation persists: Get medic	al advice/attention.		
	P362+P364 Take off contaminated clothing an			
Disposal ;	P501 Dispose of contents / container in accord	ance with local / regional / national / international regulations.		

3. Composition/information on ingredients

Substance or Mixture :

Mixture

Ingredients and concentration ranges :

Chartel	wt%	CAS No.	Global Inventories	
Chemical name			TSCA (USA)	ENCS (Japan)
Water	55≤ <65wt%	7732-18-5	Listed	-
Acetic acid ethenyl ester, homopolymer (PVAc)	20≤<30wt%	9003-20-7	Listed	Listed



Trade name : PHOTOCURE WSR SDS Number : A-340C-E2U Edited : JANUARY 3, 2017 Revised : FEBRUARY 21, 2017 Printed : FEBRUARY 21, 2017

Acrylate monomer	5≤<15wt%	Listed	Listed	Listed
Ethenol, homopolymer (PVA)	1≤<10 wt%	25213-24-5	Listed	Listed
Vinyl acetate	<0.2 wt%	108-05-4	Listed	Listed

4. First aid measures

•	r ii st alu illeasul es			
	Inhalation :	Remove victim	to fresh air and keep at rest in a position comfortable for breathing.	
		Get medical adv	ice / attention if you feel unwell.	
		Get medical adv	vice / attention if experiencing respiratory symptoms.	
		Cover body with	h blanket to warm and keep at rest.	
		Perform CPR if	not breathing.	
	Skin Contact :	Remove / Take	off all contaminated clothing immediately.	
		Wash with plent	ty of soap and water.	
		Get immediate r	nedical advice / attention, if skin irritation or rash occurs.	
	Eye Contact :	Rinse cautiously	y with water for several minutes.	
		Remove contact	lenses, if present and easy to do. Continue rinsing.	
		Rinse with clear	n water for at least 15 minutes and then seek medical attention if necessary.	
		When rinsing, o	pen your eyelids with fingers to insure saturation of water.	
		Seek medical att	tention if the problem persists.	
	Ingestion :	Rinse mouth. De	o not induce vomiting.	
		Get immediate r	nedical advice / attention.	
		Do not give an u	inconscious person anything to drink.	
		-	rs, lean patient forward or place on left side (head-down position, if possible) to maintain I prevent aspiration.	
Do not induce vomiting.			omiting.	
	Protection for personn	el administering	first aid :	
		Wear appropriat	te protective equipment if necessary.	
	Firefighting measures			
	Extinguishing media :			
	Suitable extinguishin	g media ;	Fire-extinguishing powder, fire-fighting foam, carbon dioxide, sand, water spray	
	Unsuitable extinguisł	ning media ;	Straight stream water	
	Specific hazards arisin	ng from the produ	ict :	
When exposed to high temperatures, this product may generate dangerous decompositions such as nitrogen oxides carbo monoxide, carbon dioxide, and sulfur dioxide.				
Specific extinguishing measures :		measures :	Cut off the combustion source to the origin of fire and extinguish by using the appropriate fire extinguishing media.	
			Firefighting measures should be done from windward as much as possible.	
			Take appropriate measures to disallow substances that may affect the environment from being dispersed by the drainage.	
			Remove all containers possible to a safe place promptly.	
			If not possible to remove, cool down the area. Work from windward and use respiratory equipment if necessary.	

Special protective equipment and precautions :

5.



Cut off the combustion source to the origin of fire and extinguish by using extinguishing media.

Combustion / Flue gases generate carbon monoxide and etc.

To avoid the fire from spreading, cool surrounding area with water spray.

Extinguish from windward and avoid inhaling any harmful gases. Use respiratory equipment if necessary.

Extinguish from the windward where the gases do not accumulate and prevent the leakage from spreading .

Wear appropriate protective wear (heat-proof) including air respirators.

Wear respiratory equipment for harmful gases are produced from combustion or high temperature.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures :

Avoid breathing dust / fume / gas / mist / vapors /spray.

Wear protective equipment (boots, gloves, and glasses) to prevent contact with skin.

Remove ignition sources in the area and work from windward.

Clean up immediately when it spills on the floor or any surface. (The floor surface becomes slippery).

Prohibit entry other than related personnel.

Ventilate released area.

Do not touch and/or walk in the spills.

The worker wears an appropriate protective equipment, and avoids eyes, the skin contacts, and inhalations. (refer to Item 8)

Provide adequate ventilation if indoors.

Cordon off the area and prevent entry of non-related personnel.

Work from windward and remove personnel downwind of the area.

Wear appropriate protective equipment to prevent contact with skin and inhaling fumes.

Remove ignition sources in the area promptly.

Prepare fire extinguishing equipment in case of ignition.

Environmental precautions :

Avoid releasing to the environment.

Collect spillage.

Do not empty into drain.

If it is mixed with wastewater, drain it after the activated sludge process.

Be careful not to influence living organisms and water quality in the environment by products released into rivers and any type of body of water.

Contact local authorities if it is flowing into rivers or any type of body of water as necessary.

Be careful not to influence the environment by products released into rivers or any type of body of water.

If the pollution of water pipes or waterways occur, contact relevant organizations.

Clean the area and avoid entry into plumbing system.

Be careful not drain or release untreated waste water into the environment.

Methods and materials for recovery and neutralization:

Contain the flow path with blankets or sand bags and collect into an appropriate container for large spills.

Gather and collect into a container for small spills.

Prevent the inflow into drains, sewer, basement, or enclosed areas.

Clean spills frequently as there is danger of slipping on remnants.

Remove all ignition sources.

Smoking, open flame or ignition sources are not allowed in the area.

Contain with consideration to safety.

Collect into open container by absorbing with cloths, rags, sand or etc. and then rinse with plenty of water.



Clean the spilled area with a cloth or a rag.

Wear appropriate protective equipment throughout the process.

7. Handling and storage

Relevant regulations shall be subject to where this product will be handled and stored.

Handling : Work in accordance with the Occupational Safety and Health Act and related laws and regulations.

- Keep the concentration below the allowed limit.
- Avoid inhalation and contact.
- Wear protection if risk of exposure occurs.
- Use only in a well-ventilated area.
- Avoid smoking, open flames, heat and sources of ignition.
- Always cleanse with soap and water after handling.
- Determine proper procedures for compliance.
- Seal container after use.
- Avoid leakage, overflow, dispersal and generating steam without any good reason.
- Avoid improper handling like tipping over, dropping, strong impact to or dragging the container.
- Wash hands thoroughly and rinse mouth after handling.
- Do not eat, drink or smoke when using this product.
- Do not carry contaminated gloves and protective equipment into rest / break areas.
- Prohibit entry to work areas other than related personnel.
- Collect used containers in a defined / fixed area.
- Use containers that are not damaged, corroded or cracked.
- Use local exhaust ventilation systems indoors work areas.
- Wear proper protective equipment to avoid inhalation and contact with eyes and skin.
- Storage : Store in a well-ventilated area.
 - Protect from sunlight (Ultra Violet-light).
 - Keep container tightly closed.
 - Keep cool.
 - Store in a dark light-safe area.
 - Do not freeze.

8. Exposure controls/personal protection

Management density :	Not specified.
Exposure limit values :	Not specified.
Engineering measures:	In the case of indoor use, contain at the source or install a local exhaust system.
	Provide safety shower and eye / hand wash stations and identify the area clearly.
	Contain at the source and install a local exhaust system if dust is generated.
Personal protective equipment : Wear following protective equipment as necessary and accordingly.	
	Inspect equipment on a regular basis by using a protective equipment maintenance chart.
Respiratory protection ;	Supplied air respirator, air / oxygen breathing apparatus, organic vapor gas mask
Eye protection ;	Wearing protective glasses is preferred.
Hand protection ;	Wearing gloves that organic solvents or chemicals do not penetrate is preferred.
Skin protection ;	Wearing protective clothing that organic solvent or the chemical do not
	infiltrate easily is preferred.



· · · · · · · · · · · · · · · · · · ·
:
Aqueous solution
Blue
Mild
4.0 - 6.0
Approx 0°C
Approx 100°C
Approx 1mg/cm3
dispersible, soluble
less than 0.2%
on heating and produces carbon dioxide and carbon monoxide.
rmal conditions.
open flame, high temperature, sparks, static electricity, other sources of ignition.
Incompatible with acid, alkali, amines and is prohibited to mix with.
Carbon monoxide (CO), carbon dioxide (CO2) gas might be generated by combustion.
Vapor from organic solvents.
No information available, Classification not possible based on the calculation.
Not classified. Oral, rat LD ₅₀ >2,000mg/kg
Category 5. Oral, rat LD ₅₀ =3680mg/kg
Category 5. Oral, rat LD50=2,900 mg/kg
No information available, Classification not possible based on the calculation.
Category 5. Dermal, rbt $LD_{50}=2,335 \text{ mg/kg}$
Not classified. Dermal, rat LD ₅₀ >2,000mg/kg
Category 5. Dermal, rat LD ₅₀ >2,000mg/kg
No information available, Classification not possible based on the calculation.
No information available
No information available, Category 2 based on the calculation.
Category 3. May cause irritation or inflammation if left on skin.
Corrosivity/stimulation to the skin is hardly recognized.
Category 2
No information available, Category 2 based on the calculation.
Category 2A. Causes serious damage.



·	Finited . FEBRUAR
Acrylate monomer	Category 2.
Respiratory sensitization :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients;	No information available.
Skin sensitization :	
Information on product ;	No information available, Category 1 based on the calculation.
Information on ingredients;	
Acrylate monomer	Category 1.
Vinyl acetate	Category 1.
Germ cell mutagenicity :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients;	
Vinyl acetate	Category 2.
Poly vinyl alcohol	Negative mutagenicity test using bacteria.
Carcinogenicity :	
Information on product;	No information available, Classification not possible based on the calculation.
Information on ingredients;	
Vinyl acetate	Category 2. A3/ACGIH (2001), Group 2B/IARC (1995).
Poly vinyl alcohol	Rat tests in the past show no carcinogenicity.
Reproductive toxicity :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients;	No information available.
STOT-single exposure :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients ;	
Vinyl acetate	Category 3 (respiratory tract irritation).
STOT-repeated exposure :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients;	
Vinyl acetate	Category 2 (respiratory organs).
Aspiration hazard :	
Information on product ;	No information available, Classification not possible based on the calculation.
Information on ingredients;	No information available.
. Ecological information	
Ecotoxicity :	
Information on product;	No information available, Category 3 based on the calculation.
Information on ingredients;	
Acrylate monomer	Category 2.
Vinyl acetate	Category 2 . Fish (Oryzias latipes var) L C 50=2.39mg/L/96h
Persistence and degradability :	
Information on product ;	No information available.
Information on ingredients;	
Poly vinyl alcohol	Biodegradation is carried out by sludge containing pseudomonas.

12.



Bioaccumulative potential :	
Information on product ;	No information available.
Information on ingredients;	No information available.
Mobility in soil :	
Information on product ;	No information available.
Information on ingredients;	No information available.
Other adverse effects :	
Information on product ;	The product is not allowed to run into drain or waterways.
Information on ingredients;	No information available.

13. Disposal considerations

Dispose of contents / container in accordance with local / regional / national / international regulations.

14. Transport information

Avoid direct sunlight during transportation. Confirm the container has no damage, corrosion, leakage before transportation. Take measures to prevent the load from tipping, falling and damages.

Classified as a "Substance determined to have very little or no bioaccumulation."

Verify the container has no leaks when transporting and take preventative measure when loading so that the cargo does not tip, fall or get damaged during transit.

UN classification :

UN number ;	Not applicable.
UN proper shipping name ;	Not applicable.
Transport hazard class(es) ;	Not applicable.
Environmental hazards (Marine pollutant) :	Not applicable.
Land transport ADR / RID :	Not applicable.
Maritime transport IMDG :	Not applicable.
Air transport ICAO and IATA:	Not applicable.

15. Regulatory information

The product must be used, stored, and transported in accordance with local / regional / national / international regulations.

16. Other information

Handling of described contents:

The information contained herein is given in good faith and accurate to the best of our knowledge. No warranty is given, expressed, or implied.

The product must not be used for any purposes other than those specified under heading 1 without first obtaining written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information given on this safety data sheet must be regarded as a description of the safety requirements relating to our product and not a guarantee of its properties.

Moreover, it is likely to be revised based on a revision of the law and a new finding.

This product is developed for general industry. Please use it after confirming safety in your company for special applications.

Reference citations:

Raw material company submitting MSDS

The Chemical Daily Co., Ltd. "2011 version 15911 chemical products" (2011)