

by the Manos del Uruguay design team

Versailles



MANOS
DEL URUGUAY

FINISHED MEASUREMENTS

Bust Circumference: 32 ½ (37, 40, 44 ¾, 48 ½)"

Length: 22 (23, 24, 25, 26)"

Jacket shown measures 37"

MATERIALS

Manos del Uruguay SILK BLEND (70% extra fine merino, 30% silk; 50 g, approx. 150 yds)

11 (11, 12, 14, 15) sk. Shown in #3207 Pine.

Size US 5/3.75mm ndls, or size needed to obtain gauge

Stitch markers

Cable ndl

Stitch holders

11 ¾" buttons

GAUGE

24 sts and 32 rows = 4"/10cm in St st

36 sts and 32 rows = 4"/10cm in 2 X 2 Rib

ABBREVIATIONS

DDR, Double Decrease Right: k3tog. DDL, Double Decrease Left: Slip 2 sts, one at a time, as if to knit; k1, pass 2 slipped sts over.

2 X 2 RIB (multiple of 4 sts)

Row 1 (RS): *K2, p2; rep from * to end of row.

Row 2 and all foll rows: Work sts as they appear.

1 X 1 RIB (odd number of sts)

Row 1 (RS): K1; *p1, k1; rep from * to end of row.

Row 2 and all foll rows: Work sts as they appear.

CABLE DART (worked over 7 sts)

Rows 1, 3, 5, and 7 (RS): K3, p1, k3.

Rows 2, 4, 6, 8, and 10: P3, k1, p3.

Row 9: Sl 2 sts to cn and hold at front of work; k1, k2 from cn, p1; sl 1 st to cn and hold at back of work, k2, k1 from cn.

Rep rows 1 – 10 for Cable Dart.

LOWER BACK, LEFT

CO 65 (75, 81, 91, 99) sts. Row 1 (RS): Work in 2 X 2 Rib to last 1 (3, 1, 3, 3) st(s), k to end. Cont in rib as est for 1½", ending with a WS row. Next row, dec and est St st: *K 3 (4, 4, 5, 6), k2tog; rep from * 5 times more, k 0 (0, 2, 2, 0), pm, work in rib as est to end – 59 (69, 75, 85, 93) sts. Next row(WS): Rib to m, slip m, p to end. Keeping St st and Rib as est, work 2 rows even. Next row, inc and dec: K to m, m1, slm, rib to last 4 sts, DDL, k1. Work 3 rows even, working new st as St st and working rib sts as they appear. Rep previous 4 rows until piece meas 6", ending with a WS row. Make note of what row is next in dec/inc sequence and set work aside.

LOWER BACK, RIGHT

CO 65 (75, 81, 91, 99) sts. Row 1 (RS): K1 (3, 1, 3, 3), p2, work in 2 X 2 Rib to end of row. Cont in rib as est for 1½", ending with a WS row. Next row, dec and est St st: Rib 35 (39, 43, 47, 51), pm, *K 3 (4, 4, 5, 6), k2tog; rep from * 5 times more, k 0 (0, 2, 2, 0) - 59 (69, 75, 85, 93) sts. Next and all WS rows: Work sts as they appear. Work 2 rows even. Next row, inc and dec: K1, DDR, work sts as they appear to m, slm, m1, k to end. Work 3 rows even. Rep previous 4 rows until piece meas same as Left Back, ending with a WS row and on same row of dec/inc sequence.



JOIN BACK

Work across Right piece in patt as est; using knitted CO, CO 13 sts; work across Left piece. Next row: Continue in patts as est, working CO sts as St st. Next row: patt to 3 sts before center st, pm, work Row 1 of Cable Dart over next 7 sts, pm, patt to end. Continue to work rows 1-10 of Cable Dart between markers to top of back. AT THE SAME TIME, cont to work Dec/Inc row every 4th row until all rib sts at both sides have been decreased – 97 (113, 121, 137, 149) sts rem. NOTE: when only 3 sts remain outside m, work last decs as DDR & DDL (omit the k1 at edge of work), 1 st will remain outside m, remove m. Work even until piece meas 14 (14 ½, 15, 15 ½, 16)" from first CO edge, or desired length to underarm, ending with a WS row.

Shape armholes: BO 4 (5, 6, 6, 6) sts at beg of next 2 (2, 2, 4, 4) rows, then 0 (0, 2, 0, 2) sts at beg of foll 0 (0, 6, 0, 2) rows. Dec 1 st each end every 4 (2, 4, 2, 2) rows 4 (5, 5, 7, 8) times, then every 0 (4, 0, 4, 4) rows 0 (4, 0, 4, 4) times. 81(85, 87, 91, 97) sts. AT THE SAME TIME, when armhole meas 4 ¾ (5 ¼, 5 ¾, 6 ¼, 6 ¾)" and center dart is ready to work Row 1, est side darts: work to 22 (23, 23, 24, 26) sts before center dart, pm, work Row 1 of Cable Dart, pm, work through center dart, k 15 (16, 16, 17, 19) sts, pm, work Row 1 of Cable Dart, pm, k to end.

When armhole shaping is complete and 81 (85, 87, 91, 97) sts rem, work even until armhole meas 7 ½ (8, 8 ½, 9, 9 ½)". Shape shoulders and back neck: at beg of next RS row, BO 7 (8, 8, 8, 9) sts, work until there are 19 (19, 20, 21, 22) sts on RH ndl, join second ball of yarn and BO center 29 (31, 31, 33, 35) sts, k to end. Next row: Working both sides at same time with separate balls of yarn, BO 7 (8, 8, 8, 9) sts at right shoulder edge, work to end. Cont to BO 7 (7, 8, 8, 9) sts at beg of foll 4 (4, 2, 4, 2) rows, then 0 (0, 7, 0, 8) sts at beg of foll 0 (0, 2, 0, 2) rows, and AT THE SAME TIME, BO from each neck edge 5 sts once. No sts rem.

POCKET LININGS (make 2)

Provisionally CO 26 sts. Work in St st for 7", ending with a WS row. Place sts on holder and set aside.

LEFT FRONT

CO 48 (54, 62, 68, 76) sts. Row 1 (RS): K1, p2, work in 2 x 2 Rib to last 1 (3, 3, 1, 1) st(s), k to end. Rib in pat as est for 1½", ending with a WS row. Next row, dec and est St st: Rib 35 (39, 43, 47, 51), pm, *k 4 (5, 2, 3, 3), k2tog; rep from * 1 (1, 3, 3, 4) times more, k to end of row – 46 (52, 58, 64, 71) sts. Inc 1 st at beg of next (WS) row and again at same edge every row 10 (12, 13, 15, 16) times more, and AT THE SAME TIME, every 4th row, (RS) k1, work DDR, rib to m, slm, m1, k to end. NOTE: when 3 rib sts remain outside m, work next dec as DDR. 1 st remains outside m. Remove m. When piece meas 5", place pocket: next RS row, patt to 13 sts before m; slide next 26 sts to holder, work across 13 sts of pocket lining, replace m, work across remaining 13 pocket lining sts, patt to end. 40 (46, 51, 57, 63) sts when all shaping completed. Work even until piece meas same as Back to armhole, ending with a WS row. Shape armhole: BO 4 (5, 6, 6, 6) sts at beg of next row, then 0 (0, 2, 0, 2) sts at beg of foll RS row(s) 0 (0, 3, 0, 1) times. Dec 1 st at beg of RS row every 4 (2, 4, 2, 2) rows 4 (5, 5, 7, 8) times, then every 0 (4, 0, 4, 4) rows 0 (4, 0, 4, 4) times – 32 (32, 34, 40, 43) sts rem. Work even until armhole meas 5½ (6, 6½, 7, 7½)", ending with a RS row. Shape neck: BO 5 (5, 5, 9, 9) sts at beg of next row, then dec 1 st at neck edge every other row 6 (5, 6, 7, 8) times – 21 (22, 23, 24, 26) sts rem. When armhole meas same as Back to shoulder, shape shoulder: At beg of RS row, BO 7 (8, 8, 8, 9) sts 3 (1, 2, 3, 2) times, then 0 (7, 7, 0, 8) sts 0 (2, 1, 0, 1) times. No sts rem.



RIGHT FRONT

CO 48 (54, 62, 68, 76) sts. Row 1 (RS): k 1 (3, 3, 1, 1), p2, work in 2 x 2 Rib to last st, k1. Rib in pat as est for 1½", ending with a WS row. Next row, dec and est St st: k 1 (1, 3, 1, 0), *k 4 (5, 2, 3, 3), k2tog; rep from * 1 (1, 3, 3, 4) times more, pm, work in rib pattern as est to end of row – 46 (52, 58, 64, 71) sts. Inc 1 st at end of next (WS) row and again at same edge every row 10 (12, 13, 15, 16) times more, and AT THE SAME TIME, every 4th row, (RS) k to m, m1, slm, work in rib pat to last 4 sts, DDL, k1. NOTE: when 3 rib sts remain outside m, work last dec as DDL. 1 st remains outside m. Remove m. When piece meas 5", place pocket: next RS row, patt to 13 sts before m; slide next 26 sts to holder, work across 13 sts of pocket lining, replace m, work across remaining 13 pocket lining sts, patt to end. 40 (46, 51, 57, 63) sts when all shaping completed. Work even until piece meas same as Back to armhole, ending with a RS row. Shape armhole: BO 4 (5, 6, 6, 6) sts at beg of next row, then 0 (0, 2, 0, 2) sts at beg of foll WS row(s) 0 (0, 3, 0, 1) times. Dec 1 st at beg of WS row every 4 (2, 4, 2, 2) rows 4 (5, 5, 7, 8) times, then every 0 (4, 0, 4, 4) rows 0 (4, 0, 4, 4) times – 32 (32, 34, 40, 43) sts rem. Work even until armhole meas 5½ (6, 6½, 7, 7½)", ending with a WS row. Shape neck: BO 5 (5, 5, 9, 9) sts at beg of next row, then dec 1 st at neck edge every other row 6 (5, 6, 7, 8) times – 21 (22, 23, 24, 26) sts rem. When armhole meas same as Back to shoulder, shape shoulder: At beg of WS row, BO 7 (8, 8, 8, 9) sts 3 (1, 2, 3, 2) times, then 0 (7, 7, 0, 8) sts 0 (2, 1, 0, 1) times. No sts rem.

SLEEVES (both alike)

CO 64 sts. Row 1: K1, p2, work in 2 x 2 Rib to last st, k1. Work in Rib as est for 1½", ending with a WS row. Next row: K to first p st, k2, continue in rib pat to last 2 p sts, k to end. Work 3 rows even, working sts as they

appear. Next row (RS): K until first p rib, k the 2 p sts tog; rib to last p rib, k the 2 p sts tog, k to end. Work 3 rows in pat. Repeat the last 8 rows 3 times more, until all p sts have been converted to k, and 8 sts have been dec. AT THE SAME TIME, after working 5 rows, (WS) inc 1 st at each end of next and foll 10 (8, 8, 6, 6)th row a total of 8 (10, 11, 13, 15) times. 72 (76, 78, 82, 86) sts when all shaping complete – initial rib has been dec from 64 to 56 sts, plus 16 (20, 22, 26, 30) sts increased at edges. Work even until piece meas 17" or desired length to underarm. Shape cap: BO 4 (5, 6, 6, 6) sts at beg of next 2 (2, 2, 4, 4) rows, then 0 (0, 2, 0, 2) sts at beg of foll 0 (0, 6, 0, 2) rows, then dec 1 st each end every RS row 8 (8, 3, 1, 1) times, every 4th row 4 (5, 10, 13, 14) times, every RS row 8 (8, 2, 1, 0) times – 24 (24, 24, 28, 28) sts rem. BO all sts.

BACK BELT

CO 3 sts. Work in 1 x 1 Rib and inc 1 st each end every RS row 8 times – 19 sts. Work even until piece meas 7" from beg, ending with a WS row. Dec 1 st each end every RS row until 3 sts rem. BO.

EPAULETTES (make 2)

CO 15 sts. Work in 1 x 1 Rib for 3 (3, 3 ¼, 3 ¼, 3 ½)", ending with a WS row. Dec 1 st each end every RS row until 3 sts rem. BO.

BUTTON TABS (make 3)

CO 15 sts. Work in 1 x 1 Rib for 4 rows. Next row: Rib 6, k2tog, yo, rib to end. Cont in rib until piece meas 3 ½". BO.

NECKBAND

CO 13 sts. Work in 1 x 1 Rib for 19". Do not break yarn; leave sts on holder.

FINISHING

Block pieces to measurements.

Back Vent Border: Pick up and k 32 sts along one side edge of vent. Work in 2 x 2 Rib, and inc 1 st at bottom edge every RS row until border meas 1 ½". Bind off. Work edging in same way along other side edge. Sew bottom border edges along edge of bottom ribbing. Sew top border edges to cast-on edge at top of vent.

Pockets: Remove provisional cast-on of pocket lining and replace sts on ndl. Replace held sts from front of pocket on second ndl. Holding 2 ndls parallel in left hand, with lining sts behind body sts, work together 1 st from front ndl with 1 st from back ndl in 2 x 2 Rib across row. Cont in rib as est for 1". BO. With 24" length of yarn, sew edge of rib to body, then use same strand to stitch sides of pocket lining closed.

Front Border: Pick up and k 117 (117, 121, 121, 125) sts along Left Front edge from neck to bottom, pm, then cont to pick up 17 (17, 17, 21, 21) sts along angle to ribbing. 134 (134, 138, 142, 146) sts. Beg with a WS row and p2, work in 2 x 2 Rib to end. On all RS rows, inc 1 st before and after m and at end of row. When rib meas 1 ½", BO. Sew side edge of rib at bottom to side edge of rib from body. Work Right Front Border to match.



Collar: Sew shoulder seams. Beg at right front neck edge, pick up and k approx. 12 sts along edge of ribbing, 25 (25, 27, 27, 29) sts along curve of neck edge, 48 sts along back neck edge, 25 (25, 27, 27, 29) along left front neck, and 12 sts along edge of ribbing – 122 (122, 126, 126, 130) sts. Next row (WS): Beg with p2, work in 2 x 2 Rib for 4". Dec 1 st each end every RS row until collar meas 5 1/2". BO.

Neckband: Beg at left front edge, sew neckband on outside of collar along edge where sts are picked up. Band should end approx. 1" past edge of ribbing at right front edge. Add or subtract rows as needed, then replace band sts on ndl. Next row: Rib 5, k2tog, yo, rib to end. Work 4 rows even. Dec 1 st each end every RS row until 3 sts rem. Next row: Sl 1, k2tog, pss0. Fasten off. Tack long open edge of neckband loosely to collar. Set in sleeves. Sew side and sleeve seams. Sew straight end of each epaulette to shoulder seam; tack other end down by sewing button through epaulette 1/2" from tip. Sew long edge of Back Belt to Back so that lower edge ends at top of vent; sew a button through belt 1/2" from each tip. Sew 1 button through all thicknesses of neckband and collar approx. 1 1/4" from left front edge. Sew 3 more buttons in line with first at 3" intervals down left front border. Sew a button tab to right front edge opposite each button, securing it by sewing a button through all thicknesses approx 1/2" from BO edge (thus having buttonhole in line with button on left front). Weave in ends.

