**Field and Brush Mower** 

### **Commercial Power Tools**

Model: AT45026GENG

## **UPC**: 843530005769

#### GENERAC PRO FIELD AND BRUSH MOWER

- Generac G-Force engine has power to spare for the toughest jobs.
- 26 in (66 cm) mowing deck for cutting extra tall and dense growth down with ease.
- Puncture resistant, lugged tires provide maximum traction on soft ground and side slopes.
- Power steering for better maneuverability.



### **FEATURES**

- Generac G-Force Engine: Powerful, easy starting engines make our field and brush mower the natural choice for any task, and are designed for long life.
- Power Steering: The disc brake system provides power steering. Each wheel is equipped with a hand brake, allowing for easy maneuverability.
- Superior Mulching: The mower deck processes grass and brush into a fine mulch, eliminating windrows typically produced by side-discharge mowers.
- **Gear-Driven Transmission:** Geared transmission locks in the ground speed, leaving your hands free to steer the machine across uneven terrain. Choose a fixed pace from three forward gears.
- Large Lugged Tires: Puncture resistant, lugged treads on big tires (18 in x 6.5 in x 8 in [46 cm x 16.5 cm x 20 cm]) pull the mower over and through most terrain.
- Heavy-Duty Brush Blade: The brush blade is sharp on both sides, so it can be reversed for longer use between sharpening.

- High-Performance Blade Spindle: Integrated into the deck housing, the 1.375 in (34.9 mm) thick cast iron spindle with oversized double sealed bearings is designed for vibration-free performance to provide years of maintenance-free use.
- Commercial Grade Electric Clutch: The self-adjusting clutch is designed for easy access and quick attachment swapping. No cables to stretch, or belt engagement pulleys to get out of adjustment. Extensively tested for the tough jobs.
- Built to Take a Beating: Framed in heavy-duty, powder coated, laser cut steel, and featuring reinforced key stress spots to provide reliable operation for years.
- Adjustable Handlebars and Ergonomic Control: A comfortable working height is important, especially when traversing rough terrain. Controls are integrated into the grips for operator comfort.

# **Specifications**

General	
CARB Certified	Yes
Assembly Required	Yes
Cutting	
Cutting Height	3.5 in (8.9 cm)
Cutting Width	26 in (66 cm)
Cutting Capacity	4 ft (1.2 m) high grass 8 ft (2.4 m) high weeds 2.5 in (6.4 cm) thick saplings
Engine	
Make	Generac G-Force
Horsepower	16
Air Filter Element	Dual element
Pre Cleaner	Yes
Cooling Method	Air
Displacement	27.6 in <sup>3</sup> (452cc)
Engine Type	OHV
Lubrication	Splash
Number of Cylinders	1
Oil Capacity	41 oz (1.2 L)
Oil Type	30W HD
Starting Type	Electric
Choke/Primer	Choke

Dimensions	
Shipping Dimensions	62 in x 45 in x 44 in (157 cm x 114 cm x 112 cm)
Shipping Weight	396 lbs (180 kg)
Dimensions	80.5 in x 30.25 in x 48.2 in (204 cm x 77 cm x 122 cm)
Weight	290 lbs (131.5 kg)
Fuel System	
Fuel Capacity	2 gal (7.6 L)
Fuel Shutoff Valve	Yes
Material	
Frame	12 gauge
Deck	12 gauge, pivotable
Wheels/Tires	
Dimensions	18 in x 6.5 in x 8 in (45.7 cm x 16.5 cm x 20 cm)
Number of Tires	2
Tread	Lugged
Warranty	
Machine / Engine	1 year

