



GRAVITY™
ADVANCED
WATER
PITCHER

USE AND CARE MANUAL

Model Number **GRP200**

Replacement filters are available on-line
www.clear2o.com

Before operating this product, please read these instructions completely and save this manual for further reference.

Congratulations on your purchase of the CLEAR₂O Gravity™ Advanced Water Pitcher – an easy way to enjoy cleaner, healthier, great-tasting water...right out of your kitchen faucet.

Product may vary slightly from what is illustrated.

- A. Spout Cover
- B. Pitcher Lid
- C. Pour Through Lid
- D. Filter Life Indicator
- E. Water Reservoir
- F. TrueFilter™ Pleated Cat-Ion Filter (Model # GRF201)
- G. Handle
- H. Pitcher



CLEAR₂O Gravity™ Advanced Replacement Filters
available at www.clear2o.com.

GETTING STARTED

1. Carefully unpack CLEAR₂O Gravity™ Advanced Water Pitcher, removing all packaging materials.
2. Hand-wash pitcher, lid, and water reservoir with a mild detergent and water. Do not use abrasive cleaners. Rinse well and dry.

TIP: Periodically hand-wash your pitcher, lid, and reservoir. For best results cleaning CLEAR₂O Gravity™ Advance Filter Water Pitcher lid, dilute a teaspoon of vinegar in a cup of water. Soak a soft sponge in vinegar solution and wipe clean.

Do Not Wash in Dishwasher.

3. Remove the filter from the packaging.



IMPORTANT: You must use municipally treated / private well, potable water (e.g. tap water).

*Hot water should not be used with the CLEAR₂O pitcher filter (Max 85°F / 27° C).

READY FOR CLEAR₂O GRAVITY™ ADVANCED WATER FILTER

1. Select a level countertop space. Hold the water reservoir in the upright position and lift pitcher lid to open.
2. Rinse filter under cold, running tap water for a few seconds to wet filter and remove any debris from manufacturing.
3. Insert filter into place and rotate filter clockwise until stop. Filter should be securely attached.
4. Discard the first 3 pitchers of filtered water to flush the pitcher, or use this water for plants. It is normal for carbon dust to appear in your first fillings.
5. Fill the pitcher with cold tap water through the pour through lid. Do not overfill.



6. Allow water to filter completely before pouring or refilling reservoir.
7. Close water window pour through lid when the reservoir is full.

FILTER INDICATOR

1. The CLEAR₂O Gravity™ Advance Filter Pitcher has a TrueLife™ filter life indicator built into the filter cover that automatically measures 60 gallons and resets after the filter is replaced.

- | | |
|--------|---------------------------------|
| Green | – Good for 60 Gallons |
| Yellow | – Filter is nearing replacement |
| Red | – It is time to replace filter |



2. Once indicator turns red, it time to replace the filter.

CARE AND CLEANING

1. Remove filter from pitcher
2. Hand-wash pitcher, lid and water reservoir with a mild detergent and water. Do not use abrasive cleaners. Rinse well and dry.
3. Replace with new filter; TrueLife filter indicator will be reset upon insertion of filter. Thus it is recommended to time cleanings upon filter replacement.

TIP: Periodically hand-wash your pitcher, lid and reservoir. For best results cleaning CLEAR₂O Gravity™ Advanced Filter Water Pitcher lid, dilute a teaspoon of vinegar in a cup of water. Soak a soft sponge in vinegar solution and wipe clean.

IMPORTANT: Do not wash the CLEAR₂O filter. Never place pitcher or filter in dishwasher.

Replacement filters are available on our website www.clear2o.com.

For best results, the filter should be replaced after 60 gallons of consumed water, approximately every 2 to 3 months.

Unlike some other products that estimate filter life based on a timer, the TrueLife™ filter life indicator in your CLEAR₂O Gravity™ Advanced Water system measures the amount of water you use, resulting in a better value for your money. You will not need to replace the filter unless you have exceeded the recommended filter capacity.

REMOVING & REPLACING FILTER

1. Select a level countertop space. Hold the water reservoir in the upright position and lift pitcher lid to open.
2. Remove filter by twisting counter clockwise until filter is released.
3. Remove filter from pitcher and discard or place in recycle bin.
4. Remove CLEAR₂O replacement filter from the packaging.
5. Rinse filter under cold, running tap water for a few seconds to wet filter and remove any debris from manufacturing.
6. Re-insert into place and rotate filter clockwise until stop. Filter should be securely attached.
7. Discard the first 3 pitchers of filtered water to flush the pitcher, or use this water for plants. It is normal for carbon dust to appear in your first fillings.
8. Fill the pitcher with cold tap water through the water window pour through lid.* Do not overfill.
9. Allow water to filter completely before pouring or refilling reservoir.
10. Close water window pour through lid when the reservoir is full.

OPERATING AND SAFETY REQUIREMENTS

- Water Temperature : Max 85° F – Min 34°F
- It is essential to follow the operational maintenance and filter replacement instructions for this product to perform as designed.
- Replace filter after 60 gallons of filtered water.
- Do not microwave pitcher or filter.
- Do not immerse or fill the pitcher with boiling water.
- Do not place pitcher or filter in the freezer or allow it be kept in freezing temperatures.
- Do not drink water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after using this system.
- Not intended to be used with fruit, vegetables and/or herbs.
- For best results, change water in the CLEAR₂O Gravity™ Advanced Water Pitcher every few days.

TROUBLESHOOTING

| Problem | Possible Cause | Solution |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Water bypasses filter | Filter is not seated correctly | Remove and re-insert filter correctly into place |
| Filter indicator does not change | 1) Lid is not firmly in place to trigger filter indicator 2) 60 gallon limit has not been reached 3) Filter is not seated properly | 1) Firmly push down lid to close 2) Continue to use until indicator changes 3) Remove and re-insert filter correctly |
| Filter appears green | Water Pitcher should be kept in refrigerator at cold temperature | Replace filter |

SERVICE AND WARRANTY

NEED HELP?

For service or any questions regarding your water filtration product, visit our website at www.clear2o.com. Do not return the product to the place of purchase. Do not mail the product back to the manufacturer. This product has a 90-day Limited Warranty (which applies only in the United States and Canada) when strictly used in accordance with instructions to filter municipally treated/private well, potable tap water.

WHAT DOES IT COVER?

Any defect in material or workmanship.

FOR HOW LONG?

90 days after the date of original purchase.

WHAT WILL WE DO TO HELP YOU?

Provide you with a reasonably similar replacement product.

HOW DO YOU GET SERVICE?

Save your receipt as proof of the date of sale and contact our customer service department at support@clear2o.com.

WHAT DOES YOUR WARRANTY NOT COVER?

- Damage from commercial use.
- Damage from misuse, abuse or neglect.
- Products that have been modified in any way.
- Products used or serviced outside the country of purchase.
- Shipping and handling costs associated with the replacement of the unit.
- Consequential or incidental damages (please note, however, that some states do not allow the exclusion or limitation of consequential or incidental damages, so this limitation may not apply to you)
- Damages resulting from the use of the product with a defective water faucet.



HOW DOES STATE LAW RELATE TO THIS WARRANTY?

This warranty gives you specific legal rights, and you may also have other rights that vary from state to state or province to province.

DO NOT USE THIS PRODUCT WITH WATER THAT IS MICROBIOLOGICALLY UNSAFE OR OF UNKNOWN QUALITY.

Systems certified for cyst reduction may be used on disinfected waters that may contain filterable cysts.



Visit us at our website www.clear2o.com, ,  and  for the latest product updates and social media forums.

Should you have any questions or concerns with your new product, please contact Customer Service support@clear2o.com. Please do not return to the store.



Miami Lakes, Florida 33014

All right reserved. Clear2O® is trademark of Applica Water Products, LLC.
Copyright ©2015 Applica Water Products, LLC

Made and printed in People's Republic of China..