

 thrislington cubicles	
Product: oasis ss	Contact: t +44 1244 520 677 w www.thrislingtoncubicles.com e info@thrislingtoncubicles.com
k32 Specification	

k32 oasis stainless steel

Manufacturer

Thrislington Cubicles Limited, Prince William Avenue,
Sandycroft, Deeside, Flintshire, CH5 2QZ.
t: +44 1244 520677 f: +44 1244 535670
e: info@thrislingtoncubicles.com

Specification: Overall cubicle height up to 2000mm with 150mm floor clearance.

Framework: Full anodised aluminium frame, with extruded headrail and vertical posts. Lock locates into integral receiver within vertical closing post, incorporating full length buffer.

Door: 32mm finished thickness consisting of a 30mm composite core, edged top and bottom in matching high pressure laminate, then faced both sides with stainless steel sheet, each double folded to create vertical seam in the centre of the door edge. Concealed fixings within the door allow attachment to dovetail pivot block. Suspended from aluminium headrail and located onto a bottom pivot bracket, door falls closed by means of a hydraulic closer concealed within the aluminium headrail (alternatively, the closer can be factory set to fall open). Complete with anti-finger trap clearance on pivot side of door.

Divider: 18mm finished thickness consisting of a 16mm moisture resistant chipboard core, faced both sides with stainless steel sheet, each folded to create a horizontal seam in the centre of the divider edge. Supported 150mm from the floor by an engineered 304 grade stainless steel foot, with height adjustment.

Fascia: Where required, 18mm finished thickness consisting of a 16mm moisture resistant chipboard core, faced both sides with stainless steel sheet, each folded to create a horizontal seam in the centre of the fascia edge. If a fascia exceeds the width of 100mm, it will need to be supported by a stainless steel foot.

Fittings: Engineered 303 grade brushed stainless steel lock, fixed through the door to the face plate for added strength. Lock finger housed within the door, extends from the door edge and engages into the receiver, integral to the aluminium framework. Complete with emergency release facility and buffer. Divider fixed to back wall using visible stainless steel brackets, secured by through-fixings. Stainless steel coat hook supplied as standard.

Finishes:

Door: 1mm brushed stainless steel sheet.

Divider: 1mm brushed stainless steel sheet.

Fascia: 1mm brushed stainless steel sheet.