







FOTA - Upgrade firmware via SMS.



Dynamic APN – Automatically detects & sets APN.



Check signal level and view APN status via SMS.



store up to 4 cell phone numbers to receive an SMS notification (customizable) when relay is triggered etc



2 amp power supply.



Add up to 250 time restricted caller ID numbers.



Trigger, latch and unlatch SMS replies added. Ability to disable.



Auto clock sync.



3rd Gen surge protection.

MESE



Set 'Do Not Disturb Times' to avoid callers during times.



Prox (RFID) option.




Network Options



NEW AES PRO APP, user friendly. With Installer and homeowner capabilities.

		Technical Details	
Dial Out Numbers	4	Relays	2
Permanent Codes/cards	250	Relay Type	N/C and N/O
Time Restricted Codes/cards	250	Relay Load	2 amps, 24v ac max
Temporary Codes/cards	50	Power Consumption	300mA on dial out, 2amp peak demand
Automatic Trigger Events per Week	50	Modem Models	4G USA
Caller ID Numbers	250	Power Supply	24v dc (24v 2A dc adaptor included)
Time Restricted Caller ID Numbers	250		







Pedestal Panels



PRIME7-PBK-US

Pedestal panel with keypad, constructed from marine grade stainless steel, powder coated aluminium hood and gloss black toughened acrylic faceplate.

Non-Keypad panel: PRIME7-PB-US



PRIME7-PSK-US

All stainless, marine grade steel pedestal mount cellular intercom. Illuminated call button & keypad. Complete with power supply & built in antenna.


NON-Keypad panel: PRIME7-PS-US

PRIME7-ARC-RBK-US (Black panel)

PRIME7-ARC-RSK-US (Steel panel)

ARC all black keypad panel with

blue ring illumination.



Architectural panels







PRIME7-AB-US

PRIME7-ABK-US (Keypad panel)

Stylish curved architectural model. Constructed from BS316 marine grade stainless steel and finished with gloss black acrylic trim. Blue backlighting.



