

# DOLCM/SWIHIDEM

## Wiegand Card Reader




### FEATURES

- Proximity
- 26 bit Wiegand
- Reads HID® compatible and EM cards and FOBS
- Mullion mount (DOLCMWIHIDEM) or Single gang mount (DOLCSWIHIDEM)
- Waterproof (Outdoor/Indoor Rated)
- Operates in extreme temperatures: -40°F to 140°F



### SPECIFICATIONS

Frequency	125 KHz
IP Rating	IP66 (NEMA 4)
Output Format	HID Wiegand 26-Bit, EM Wiegand 26-Bit
Temperature Rating	-40°F to 140°F
Proximity Card Reader	EM & HID®
Read Range	1-3 Inches
Operating Voltage	9~18V DC
Dimensions	DOLCMWIHIDEM: L 4-3/4 x W 1-7/8 x H 7/8 " DOLCSWIHIDEM: L 4-3/4 x W 3 x H 7/8 "
Standby Current:	≤ 25mA
Housing	ABS Shell



**MOBILE CREDENTIALS AVAILABLE  
USING SYNQ**

Ask your sales rep about SynQ today!



2480 South 3850 West, Suite B  
Salt Lake City, UT 84120  
(866) 975-0101 • (866) 975-0404 fax  
www.transmittersolutions.com

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.